




FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

VACCO Vacuum Pump Oil ISO32,46,68,100



200L



18L



4L

Description:

The series of lube oil is a refined mineral oil containing high temperature and extreme pressure additives, so it can be operated at high temperature as usual. In addition, it contains many additives such as oxidation resistance, wear resistance and rust resistance, and its carbonization degree is very low.

Purpose :

The vast majority of vacuum pumps include screw pumps, vane pumps, screw pumps, etc.

Performance characteristics :

- Save energy.
- Reduce mechanical maintenance.
- Prevent the formation of a glue.

Products Code	Packings	Capacity
I100052-4L	Can	4L
I100052-18L	Pail	18L
I100052-200L	Durm	200L

Typical Physical Properties:

ISO Grade	DENSITY 20 °C , g/cm ³	FLASH POINT °C	POUR POINT °C	VISCOSITY 40°C mm ² /s	COPPER CORROSION 100 °C, 3 hrs
32	0.84-0.89	>220	<-12	28.8~35.2	1a
46	0.84-0.89	>220	<-12	41.4~50.6	1a
68	0.84-0.89	>220	<-12	61.2~74.8	1a
100	0.84-0.89	>220	<-12	90~110	1a