



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET



RUST KING Y



Description:

The rich high mineral special rust inhibitor is refined with refined mineral oil and special antirust additive with permeability and water displacement capacity. It is mainly used for the protection of iron and steel objects.

Products Code	Packings	Capacity
I100137-4L	Can	4L
I100137-18L	Pail	18L
I100137-200L	Durm	200L

Advantage:

- paraffin oil and special additives enable the product to form a protective film on the surface of the protected metal to prevent harmful chemical exposure to the metal surface. Good water displacement ability ensures that the protective film formed is also waterproof, and the special anti rust agent makes the product have the largest corrosion resistance. Good penetration characteristics enable it to penetrate into a thin contact which is difficult to reach in general protective agents, so the use of this product as a protective agent is safe.
- This product has strong penetrability and can be directly penetrated to the bottom of the thick rust layer. So it can hardly be used for grinding the metal surface before applying this product. It can be applied directly. Strong penetration also makes it easier to remove metal rust. Of course, no serious rust metal surface will be added to the product directly, so there is another economic problem.
- Low cost, the protective film formed by this product has a strong self sealing property, so even if there is scratch or brush injury, there is no need to repair the protective film. In this way, from the perspective of rust prevention, the total cost of using this product is lower than that of ordinary protective paint
- Easy to remove, the soft protective film formed on the metal surface of the product can be cleaned with petroleum solvent or kerosene. After processing, processing or processing into finished products directly exposed to the outdoor steel objects, the bottom coating of traffic vehicles, transformer shell, bridge and floating bridge buoy, storage tank, ballast box, gas cabinet, lifting equipment, farm implements.

Typical Physical Properties:

RUSTKING Y	Standard value
Appearance	Brown yellow transparent liquid
viscosity (40℃)	4.0~5.5
Flash point, ℃	≤120
Salt spray test, H	≤24

Matters needing attention:

1. Pay attention to sealing and preserving oil products