



**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

## FUTIP PLUNGER TIP LUBRICANT



### Description:

The lubricant is used as a lubricant to prevent the hard and brittle wear of the head, sleeve, and movable neutrons. It has the use of brush paint and automatic lubricating device, containing graphite particles and various types without graphite.

Products Code	Packings	Capacity
I100162 (63) -4L	Can	4L
I100162 (63) -18L	Pail	18L
I100162 (63) -200L	Durm	200L

### Purpose :

High temperature, resistance to strong impact, and the various parts, with superior lubrication, and choose to match the most appropriate base oil, graphite powder and other additives to form a strong lubrication, heat-resistant leather film.

### Performance characteristics:

- it can prevent the hard and brittle wear of the head, sleeve and so on
- the ejection mechanism operates in the best condition, and the pressure can be fully produced to produce high quality fine products.
- It can avoid corrosion of products, protrusion, sleeve, or automatic lubrication to help product corrosion, or plug through holes, or gas gas that is harmful to the human body, and especially for these points to choose raw materials carefully, so it can be used in peace.

### Typical physical properties

Model	DENSITY g/cm <sup>3</sup>	FLASH POINT °C	Whether or not graphite contains graphite	VISCOSITY 40°C	Appearance
PG-1	0.85~0.95	≥220	Contain	—	Black liquid
PG-2	0.85~0.95	≥220	Not containing	—	Yellow liquid

### Matters needing attention:

1. Pay attention to sealing and preserving oil products