



富高

FUKKOL

一切決擇於潤滑

产品描述及数据参数



FORMING OIL

Description:

FUKKOL FORMING OIL is a low viscosity lubricant. It contains fatty oil and solvent refining low aromatic mineral oil, which can provide good lubrication and extreme pressure efficiency.



Products Code	Packings	Capacity
I100217 (20) -4L	Can	4L
I100217 (20) 18L	Pail	18L
I100217 (20) -200L	Durm	200L

Performance characteristics :

It is an excellent lubricant. It is suitable for drawing, drawing, deep drawing and forming, including cold forging. It can also be used for die forging, punching, shearing and slicing. It can also be used to reduce the rolling copper pipe and stainless steel tube, deep drawing copper tube and high nickel alloy, helping to reduce the radius and thickness of workpiece movement suitable for the general processing of copper tube and the external lubrication of cold rolling.

Typical physical properties

	32	150	450	600
Appearance	Light yellow and transparent			
Copper corrosion (100℃ ,3h)level	1a			
Kinematic viscosity (40℃) ,mm ² /S	28.8~35.2	135~165	405-495	540-660
Density,g/cm ³	0.83~0.90			
Moisture,%	0%			
Flash point , °C	≥180	≥180	≥180	≥180

Matters needing attention:

1. Pay attention to sealing and preserving oil products