



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET



200L

18L

4L

KILOPOISE Resistance grease



Description:

The high damping ester is a viscous oil with special highly viscous grease and thickener. Better adjustment and lubrication of mechanical operation process, and provide a stronger adhesion. The high damping ester 40L can be used for the sliding and rotating parts of the piezoelectric devices, especially out of box board, tape and video board, instrument, spinning object, injection molding and

stationery.

Purpose :

It is suitable for block buffer parts of all kinds of precision instruments.

Products Code	Packings	Capacity
I100298 (303) -4L	Can	4L
I100298 (303) -18L	Pail	18L
I100298 (303) -200L	Durm	200L

Performance characteristics :

- Excellent performance of block and damping.
- extremely excellent adhesion properties.

Typical physical properties:

KILOPOISE DAMPING GREASE	NLGI	Kinematic viscosity 100°C CST	Flash point °C	Appearance
20	-	1000	>200	Light yellow / colorless semid
40	-	2000	>220	Light yellow / colorless semid
60	-	4000	>220	Light yellow / colorless semid
20L	-	-	>200	Light yellow / colorless semid
40L	-	-	>220	Light yellow / colorless semid
60L	-	-	>220	Light yellow / colorless semid

Matters needing attention:



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

1. Please use it in a suitable temperature range, so as not to cause the grease to freeze or melt.
2. Sealed storage.