



富高

FUKKOL

一切决擇於潤滑

产品描述及数据参数

MOULD RELEASE SERIES FUKKOL MOULD RELEASE AGENT (NON PAINTABLE)



Description:

FUKKOL MOULD RELEASE AGENT (non paintable) is a high purity release agent which does not contain harmful substances in human body. The thermal stability is good. Complex die for precision and multi row position.

Precautions:

Pressure vessels, avoid direct sunlight, stored at temperatures below 50 degrees.
Do not stamp or burn the container.
It should not be sprayed to the surface of a flame or incandescent metal.
Inflammable Materials.

Products Code	Packings	Capacity
I26696-500ML	Can.	500ML
I26696-18L	Pail.	18L
I26696-200L	Dum.	200L

Performance Characteristics:

- Hyperfine injection makes the whole die fully covered
- Increase the degree of smoothness and reduce the risk of overspraying
- Reduce the problems caused by marking and transportation, quick and effective demoulding and economic benefits. It can be demolde many times with only one spray.
- The highly effective and durable lubricating film can provide multiple demoulding, better than other silicone formulations.
- Little environmental impact, no chlorinated fluorocarbon (CFC) propellant.
- Non polluting characteristics are excellent lubricants commonly used in textile and paper industry.

Typical Physical Properties:

APPEARANCE	ODOR	COPPER CORROSION 100 °C,3 hrs	VOLATLLE%	DENSITY 25 °C , g/cm ³
Water clear	Solvent odor	1a	95.5~97.5	0.7~0.75