



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

MOULD RELEASE SERIES FUKKOL MOULD RELEASE AGENT (PAINTABLE)



Description:

High efficiency and no superdry mold release agent is a kind of spray demoulding agent containing high efficiency silicone, which provides quick release to most plastic and rubber products formed by injection mold, and it is effective and pollution-free.

Precautions:

Pressure vessels, avoid direct sunlight, stored at temperatures below 50 degrees.

Do not stamp or burn the container.

It should not be sprayed to the surface of a flame or incandescent metal.

Inflammable Materials.

Products Code	Packings	Capacity
I23321-500ML	Can.	500ML
I23321-18L	Pail.	18L
I23321-200L	Dum.	200L

Performance Characteristics:

- Hyperfine injection makes the whole die fully covered
 - Increase the degree of smoothness and reduce the risk of overspraying
 - Reduce the problems associated with marking and shipping, and are quick and effective.
- Demoulding and economical efficiency, it can be demolde many times with only one spray.
- The highly effective and durable lubricating film can provide multiple demoulding.
 - Little environmental impact, no chlorinated fluorocarbon (CFC) propulsion.
 - Non polluting characteristics are excellent lubricants commonly used in textile and paper industry.

Typical Physical Properties:

APPEARANCE	ODOR	COPPER CORROSION 100 °C, 3 hrs	VOLATLLE %	DENSITY 25 °C , g/cm ³
Water clear	Solvent odor.	1a	95.5~97.5	0.7~0.75