



TIECHINICAL DATA SHEET



METAL SURFACE BALANCE DETECTOR SPRAY-RED PASTE



Description:

FUKKOL Metal surface balance detector Spray – Red Paste is a high-quality performance it had made from synthetic solvent, leveling agents, non-fading pigment preparation, can be used to detect the machine parts surface defects, machine parts installation checking or mold surface matching inspection, easy to identify defects and marking the problem position. It suitable for smooth or matte surfaces.

Features:

- -Mould matching check
- -Metal parts defect check
- -Allows clear, sharp definitions..
- -. It won't peel off
- -Resists wash off, ie. Water mix cutting fluids.
- -Easy to apply and remove.





TECHNICAL DATA SHEET

Directions for Use:

- Metal surface balance detector Spray Red Paste should be applied to a grease/dirt free surface.
- Shake well, hold upright and spray from a distance of 15-25cm (6-8ins).
- Allow film to dry for a minimum of 2 minutes before use. Ensure adequate ventilation.

N.B. To avoid blockage, clear spray head after use by inverting can and depressing button for 2-3 seconds until jet is cleared.

FUKKOL Metal Surface Balance Detector Spray – Red Paste can be easily removed with the use of a suitable solvent – FUKKOL Crackcheck Cleaner

Technical Data:

Appearance : Red , dry film

Propellant : Butane/Propane

Solvent : Acetone

Flash Point : <0°C

Storage: Temperature should be kept below 50°C.

Storage area should be out of direct sunlight.





TIECHINICAL DATA SHEET

Pack sizes and Part Codes:

500ml - Spray

500ml - Brush

Part Code

11336- S- Spray

11336-B- Brush

Health and Safety:

Safety data sheet is available from the Customer Service Department,