



500ml







NX Colorless Corrosion Inhibitor

Ref:99281

Description

- •Semi-Dried, no stripping even scratched by hand.
- •Super-Strong rust preventing property in adverse conditions cause by outdoor moisture, saintly and chemical or corrosive environment.
- •Suitable used as long-term indoor and outdoor rust preventing agents.
- Can be used as ;lubricant and anti-corrosive agent for the hinges of bonnet and boot.

Application

- •Indoor and outdoor storage for ferrous material and machinery.
- Corrosion-Protection for machinery. Like iron plate, ferrous Material of garage, pump, house or factory near the sea.
- •Weld surface under chassis and inside of fender, locker panel.

- Semi-dry, hard film, will not be wiped off with hand touch.
- Provides excellent anti rust protection outdoors no matter under wet, salty, or chemical condition, or in the corrosive and other harsh environment.
- Most suitable for long term anti rust protection indoors and outdoors.
- With penetrating property that could spray an anti rust film even for tiny parts.

DRY FILM VCI ANTI RUST SPRAY

Ref:100036

Description

High gasification antirust agent is a protective agent designed for anticorrosion requirements on the mold. It has the function of fast film forming and strong permeation. Its unique super thin film and volatile molecular weight retaining membrane can be automatically removed during the injection process.

It ensures that contaminated products will not flow out and stay in the process. Nitrite and nitrate, which do not contain nitrous acid, such as bicyclic hexyl ammonium, are safe. There is no effect on the plastic.

Application

- 1. suitable for precision molds, export molds, mold manufacturing, mold preservation
- 2. it is applicable to rust prevention of parts during processing, storage and transportation of mechanical equipment

- -Super thin film, volatile molecular weight protection membrane
- -Outdoor air, salt, chemical or corrosive atmosphere or harsh conditions, can play an excellent anti-rust power.
- It will not clog pores. Even wrinkles and mirror processing molds can be cleaned without any effect.
- Even if used for injection moulds, there will be no oil stain from the first injection after the mold is pressed.
- operating temperature range -40°C—110°C.



500ml









500ml







PEELABLE PROTECTIVE FILM COATING

Ref:84668

Description

The high peeling metal protective film is a kind of "rustproof" rust protection. Antifouling products are suitable for electroplating and grinding of metal molds and mechanical products. The surface protection function has the effects of rust prevention, scratch resistance and dirt resistance. Dry and hard After forming the light blue or translucent protective film, the toughness is very good and not easy to break.

Damage can be easily removed without need, and no cleaning agent is needed. Tearing apart The products after the membrane are bright as new. The formula contains a gasification antirust agent, which can be released. Anti rust components are filled with packing space to provide excellent rust preventive effect.

Application

- 1.Pre-process: Clean up object surface to remove all the dirt and grease with cleaning agent, solvent or alcohol then wait for it dry.
- 2. Using masker tap to cover the area not need to spray.
- 3.How to spray: Keep the nozzle 20 ~ 25cm above the surface when spray, then wait for 10 ~ 15 minutes to spray second layer. We suggest you spray at least two layer for more even coating and better protection.
- 4.The touch dry time is about 30 ~ 40 minutes, and the fully hardness dry time at room temperature is about 2 hours.
- 5.Ever film layer is about 0.015 ~ 0.020mm thickness and the best thickness the about 0.05mm. If the film layer is too thin it may difficult when peeling.
- 6.If the film is too thin and unable to peel, just spray few more on then it can be peel off.
- 7.Do NOT apply onto acrylic or wood surface. It is due to solvent may damaging the material.
- 8.After use, please press the can upside–down for few second and clean to prevent block the nozzle.

- 1.The dried film is nontoxic, acid and alkali resistance water-proof, antifouling and Anti-rust.
- 2.The spray has short drying time and good electricity insulation. Thetrans parency of the film is depending on how much moisture in the air during process.



500ml







FUKKOL RUSTKING S

Ref:12231

Description

The high and multipurpose antirust agent is made from high melting point wax paste and special rust inhibitor additive with permeability and water displacement capacity. It is mainly used for the protection of iron and steel objects.

Application

After processing, processing or processing into finished products directly exposed to the outdoor steel objects, the bottom coating of traffic vehicles, transformer shell, bridge and floating bridge buoy, storage tank, ballast box, gas cabinet, lifting equipment, farm implements.

- -Paraffin oil and special additives enable the product to form a protective film on the surface of the protected metal to prevent contact between the harmful chemical toxins and the metal surface. Good water displacement ability ensures that the protective film formed is also waterproof, and the special anti rust agent makes the product have the largest corrosion resistance. Good penetration characteristics enable it to penetrate into a thin contact which is difficult to reach in general protective agents, so the use of this product as a protective agent is safe
- -Low cost, the product formed by the protective film has a strong self sealing characteristics, so even if there is scratch or brush injury, there is no need to repair the protective film. Thus, from the perspective of rust prevention, the total cost of using this product is lower than the cost of using ordinary paint.
- -Easy to remove, the soft protective film formed on the metal surface of the product can be washed easily with petroleum solvent or kerosene



500ml







5 in 1FREEZE & DISMANTLE

Ref:88679

Description

The high freeze screw loosening agent uses instantaneous freezing to cause the components to shrink, and the instant freezing at -40 $^{\circ}$ C can help quickly and effectively loosening the bitten and corroded screws.

The resulting rust layer cracks guarantee the penetration of the product's lubricating components; the special formulation of the lubricating oil is designed to allow the lubricating components to penetrate rapidly into the rust layer; after the screw is loose, the components will be lubricated and protected from corrosion.

Application

It is used to solve the occlusal and corrosion problems of screw and cylindrical components in all industries, including cars, trucks, farm and construction machinery, and general industry.

- 1.Shock freezing(It can reach -40°C when you continuously spray the aerosol with 7 seconds)
- 2.Ensure the nuts and bolts will not be transformated, warpped, slipped angle with excessive strength.
- 3. Save time and money in dismantling the screws.
- 4.multifunctional special lubricants five in one with the characteristic of Freeze, Penetrate, Lubricate, Remove rust and Anti-rust.



500ml







FUKKOL MOULD PROTECTOR (GREEN)

Ref:11334

Description

The high and long term rust inhibitor is an ultra-thin green rust inhibitor, such as a protective film with green pigments, which is convenient for identifying the surface.

Long term rust inhibitor can provide lubrication and long-term rust protection. It can be automatically removed in the injection process, and there is no need to clean it before production.

Application

Provide a layer of ultra thin green antirust soft film, absolute drainage and moisture proof, provide longterm antirust protection for metal.

It is especially suitable for plastic mould and die casting mould in production and storage. It also applies to other metal tools and parts.

- -Contains a green dye to identify treated surfaces
- -Simply removed by putting mould back in service
- -Provides complete protection against finger-print
- -Provides corrosion protection for more than 2 years (indoor)
- -No CFCs, ozone friendly.



500ml







RUSTER WAX

Ref:56686

Description

High white medium antirust agent is a multi-purpose antirust agent. It is suitable for gear, bearings, fasteners and other parts and facilities, including moulds, sliding parts, and other exposed surfaces stored in indoor equipment for general corrosion protection.

Application

Antirust sprays are ideal for rust protection of machined parts exposed to metal surfaces and storage, transportation and working procedures.

The dry protective film produced by the antirust sprayed spray is automatically removed during the injection process, and there is no need to clean the parts after processing or using. This product is packed in a convenient aerosol tank and is the ideal antirust agent in the workshop

Benefits

Ultra-fine indoor corrosion resistance
Forms a soft protective film
Generally, component surfaces need no degrease treatment
Good protection under damp environment
Aerosol dispenser for convenience
CFC-free.



500ml







FOOD GRADE ANTI-RUST SPRAY

Ref: 11994

Description

The high food grade antirust agent is a non-toxic and FDA antirust lubricant, which is refined from a deep refining mineral base oil, an aluminum thickener and a very effective extreme pressure additive.

Application

It is mainly used in non-toxic occasions such as door cabinet, gear and chain of food machinery, food, medicine, cosmetics, washing device, filling device, handling device and so on.

- -Good anti-rust and de-watering performance
- -Film can be removed by common de-oiling method
- -Soft Film
- -Easy of Application



500ml







RUSTKING L

Ref:48892

Description

The high and super long period rust inhibitor is a kind of dura coffee rust inhibitor, such as a protective film with coffee pigment, which is convenient for identifying and identifying the applied surface.

Super long - term antirust agent can provide lubrication and long-term protection, not more than 50 C \sim 60 C antirust film will not melt, in the room can play not less than 5 years of antirust period, in the outdoor can play not less than 3 years of rust, in the process of automatic injection process without cleaning before the automatic removal of production.

Application

Provide a layer of coffee color antirust membrane, absolute drainage corrosion prevention and moisture-proof, in wet environment also get a safe protection for metal to provide ultra long rust protection function.

It is especially suitable for heavy machinery, plastic moulds and metal products, and is also suitable for power plants and ocean going ships.

- -Contains a brown dye to identify treated surfaces
- -Simply removed by putting mould back in service
- -Provides complete protection against finger-print
- -Provides corrosion protection for more than 5 years (indoor)
- -Provides corrosion protection for more than 3 years (outdoor)



450ml







FUKKOL GILL 6

Ref:31131

Description

The high circuit board protective paint is the most ideal protective paint for the circuit board and electronic parts. It prevents the corrosion of the circuit by the dilute acid, salt liquid and water gas, forms the ideal insulation and protection film, and eliminates the leakage and short circuit.

It is stable in nature and can play a satisfactory protective effect at a temperature of up to 90°C and low at -70°C. It is especially suitable for protecting the electronic equipment of temperature unstable or humid.

Application

- -This product can be used in many applications and provide long-term corrosion protection
- Protection of PCB from alkali, acid, salt, water vapor and other erosion, to prevent circuit board short circuit and oxidation
- -Protect the antenna and protect the V.H.F. The television and radio antennas are not subjected to air corrosion, and he can also seal the antenna connection box, and the antenna (two to 31 transmitters share the antenna) interference elimination device, antenna wave filter, etc., will not applement a water
- -Marine radio, as an insulating paint, can prevent leakage of electricity from coils and transformers, insulate cables and conductors, and prevent alkaline water from eroding parts.

- -Only need to spray 3 layers to provide dielectric resistance against 16KV
- -Circuit board sprayed by this product can be coated with tin.
- -CFC-free.
- -Forms a highly insulate transparent thin film.



500ml







FUKKOL MOULD RELEASE AGENT NON-PAINTABLE

Ref:17791

Description

High oil demoulding agent is a highly efficient spray demoulding agent, which provides fast, effective and non polluting molding for plastic and rubber products formed by most injection moulds. The specially designed nozzle can produce very fine spray effect, and the spraying quantity can be completely controlled, even the most complicated mold cavity can be completely covered.

Application

- -Ultra fine spray gives controlled application with complete coverage
- -Improved finish and reduced risk of over application
- -Reduces problems associated with marking and transfering, highly economical, efficient release, only one pass required for many shots of ejection
- -Effective and long lasting film provides more numbers of release than most silicone formulations
- -Low environmental impact, contains no CFC propellant Nonstaining property makes it an excellent lubricant for textile and paper industry.

Benefits

Pressure container, protect from sunlight, store at tempera -ture below 50°C

Do not puncture or incinerate the can

Do not spray on to naked flame

Flammable.

500ml







FUKKOL MOULD RELEASE AGENT (NON-PAINTABLE)

Ref:26696

Description

FUKKOL MOULD RELEASE AGENT (non paintable) is a high purity release agent which does not contain harmful substances in human body. The thermal stability is good. Complex die for precision and multi row position.

Benefits

- -Ultra fine spray gives controlled application with complete coverage
- -Improved finish and reduced risk of over application
- -Reduces problems associated with marking and transfer, highly economical, efficient release, only one pass required for many shots of ejection
- -Effective and long lasting film provides more numbers of release than most silicone formulations
- -Low environmental impact, contains no CFC propellant

Non staining property makes it an excellent lubricant for textile and paper industry.

Precautions

Pressure container, protect from sunlight, store at tempera -ture below 50°C

Do not puncture or incinerate the can Do not spray on to naked flame Flammable.



500ml







FUKKOL MOULD RELEASE AGENT (PAINTABLE)

Ref:11881

Description

The high dry release agent is a spray release agent, which provides fast speed for most plastic and rubber products molded by injection moulds.

Czechoslovakia, effective and uncontaminated, high dry stripping agent is specially developed for some products that need to be carried out in incidental process, such as printing, paint, electroplating, hot stamping and pressing welding, which require no "silicone problem".

Benefits

*Ultra fine spray gives controlled application with complete coverage

*Improved finish and reduced risk of over application

*Reduces problems associated with marking and transfer, highly economical, efficient release, only one pass required for many shots of ejection

*Effective and long lasting film provides more numbers of release than most silicone formulations

*Low environmental impact, contains no CFC propellant

*Excellent for all thermal plastic, especially ABS and PS

*Will not affect subsequent operations.

*Excellent lubricant for sewing threads, table surface, needles and knives

Precautions

Pressure container, protect from sunlight, store at tempera -ture below 50°C

Do not puncture or incinerate the can

Do not spray on to naked flame

Flammable.

FUKKOL TRANSPARENT PLASTIC MOULD RELEASE AGENT

Ref:19938

Description

The high transparent plastic release agent is specially made for most common injection, extrusion and hollow plastic transparent plastic products. Its unique super dry powder can effectively solve the problem of oil pollution on the surface of the traditional products.

Therefore, this product can be used in the process operation, such as injection, electroplating or screen printing, not containing silicon. Chemical composition of ketone chloride.

Application

Excellent for use in:

- 1. ABS, PC, acetal, acrylic, PE, PP, Nylon, Pom, PS, epoxy, and all rubber.
- 2. Computer components, optical lens, transparent plastic case, plastic board, or rubber products.

- *Colourless, non-toxic and non-staining, excellent for use in food, paper and textile industries.
- *Heat stable, non-transferring, non-conductive.
- *Good lubrication for ejector pins with high moulding temperature.
- *Heat stable at operating temperature up to 350° C.



500ml















FUKKOL MOULD RELEASE AGENT (PAINTABLE)

Ref:23321

Description

High efficiency and no superdry mold release agent is a kind of spray demoulding agent containing high efficiency silicone, which provides quick release to most plastic and rubber products formed by injection mold, and it is effective and pollution-free.

Benefits

- *Ultra fine spray gives controlled application with complete coverage
- *Improved finish and reduced risk of over application
- *Reduces problems associated with marking and transfer, highly economical, efficient release, only one pass required for many shots of ejection
- *Effective and long lasting film provides more numbers of release than most silicone formulations
- *Low environmental impact, contains no CFC propellant
- *Non staining property makes it an excellent lubricant for textile and paper industry.

Precautions

Pressure container, protect from sunlight, store at tempera -ture below 50°C

Do not puncture or incinerate the can Do not spray on to naked flame Flammable



500ml







FOOD GRADE SILICONE SPRAY

Ref: 11993

Description

High food grade demoulding agent is a spray demoulding agent, which provides fast, effective and non polluting molding for plastic and rubber products formed by most injection moulds.

High quality plastic and rubber products are suitable for home appliances and electrical equipment manufacturing industry. In addition, this product is specially developed for some products that require incidental working procedure, such as printing, paint, electroplating, hot stamping and pressing welding, which require no "silicone problem". NSF H1 certification is suitable for occasions where food and food are available.

Application

Uitra fine spray gives controlled application with complete coverage.

Improved finish and reduced risk of over application.

Reduces problems associated with marking and transfer, highly economical, efficient release. Only one pass required for many shots of ejection.

Effective and long lasting film provides more numbers of releases than most silicone formulations.

Low environmental impact, contains no CFC propellant. Will not affect subsequent operations.

Benefits

*Shake well, hold upright and spray from a distance of approximately 20cm. One pass usually provides sufficient coating. Pressurised container, protect from sunlight, store at temperature below 50°C

*Do not puncture or incinerate the can

*Do not spray on to naked flame

*Inflammable



500ml







P. T. F. E MOULD RELEASE AGENT

Ref: 76349

Description

The high fluorine release agent is a silicon free dry release agent, which makes the stripping operation fast, effective and clean. No matter how complicated the mold is and how meticulous the road patterns are, it can still reliably reproduce the model contour.

This product is applicable to all plastic and rubber moulds, including injection molding, compression and blow molding. This product can evenly penetrate into the various parts of the most complex mold, giving you a safe and clean release function.

Its dry film will not affect the contour of the finished product or prevent the precise combination. The coating film has good adhesion, and it will not be contaminated or transferred to the finished product. It is safe and reliable. It is not afraid to produce defects. It will not be harmful to the subsequent polishing process.

Application

*Effective release of plastics and rubber moulded parts.

*Thin film - will not affect profiles or interfere with precision fits.

*Will not affect subsequent finishing operations

*Silicone free.

Benefits

*Shake well, hold upright and spray from a distance of approximately 20cm. One pass usually provides sufficient coating. Pressurised container, protect from sunlight, store at temperature below 50°C.

*Do not puncture or incinerate the can.

*Do not spray on to naked flame.

-Inflammable.



500ml







FUKKOL PTFE LUBE

Ref:22348

Description

This product is a high quality high temperature thimble oil, with high quality lubricity and viscosity under high temperature and high pressure. It provides a good dry lubrication film for the surface of all kinds of materials.

Application

It is used for precision instrument, clock, high speed textile machinery, factory conveyor belt, electric motor (engine), guide rail, vending machine, rolling and sliding device, bearing in high temperature environment.









EJECTOR PIN LUBRICANT

Ref:36686

Description

This product is a multi-purpose lubricant, which is specially formulated to resist corrosion, abrasion and lubrication for thimble of plastic injection molding machine.

Application

FUKKOL Ejector Pin Spray should be used for the protection of ejector pins used on injection moulding machines. This product is suitable for use on all types of plastic injection moulding machines and in compatible with almost all types of plastics in current using.

The synthetic oil and additives contained in this product ensure a good anti-oxidant ability at high temperature, and the advanced lubricity additives enable a continuous lubricating in the processing of fast circulating operation and short time plastic hardening process.

- -Excellent anti-wear properties
- -Close todry film
- -Good corrosion resistance
- -Resistant to high temperatures
- -Excellent lubricity
- -Easy to apply
- -Convenient aerosol pack
- -CFC free



500ml







FUKKOL POWER LUBE

Ref:11448

Description

The thimble oil, refined from crude oil, contains a lot of extreme pressure additives. It can be used for high load sliding part and plastic top pin

Application

- *For lubricating slide ways under all conditions of speed and load.
- *Particularly suitable for centralized lubrication systems.
- *For lubricating wide range of products including all parts of machinery tools. (hydraulic, slides, gears)
- *Designed for use for steel/steel & copper/Iron slide ways.
- *Also be used for machinery tools using same slide ways lubricating system or in same hydraulic system.
- *Use for plastic pins.

- -High quality oils of good oxidation stability with oiliness, antiwear & tackiness additives which impart the frictional characteristics necessary to prevent 'stick-slip' in tableways & slideways' operations.
- Protects exposed machine tools parts from corrosion.
- -Perfect neutrality to oil seals.
- -Excellent demulsibility.
- -Very good resistance to oxidation.
- -Very good anti-rust protection.
- -Very good anti-wear protection.



500ml







MOLYFU SPRAY

Ref:66466

Description

FUKKOL Molybdenum disulfide antiwear agent, Special reinforced molybdenum disulfide powder, Effectively reducing metal friction and improving working load.

FUKKOL Molybdenum disulfide antiwear agent can be used in metal, Rubber and areas requiring dry lubrication, The unique dry powder can effectively protect the metal surface from oil pollution. Make it increase the use cycle of the product, The product has good anti chemical and water resistance, Therefore, it can be considered in some harsh environments, Suitable for working environment within 400°C.

Application

It is recommended to use the gasket . Conveyer belt and bearing . Automatic and manual mechanical equipment for motor equipment, Or can be used for gears and guideways, Lubrication of most sliding mechanical parts in cam and regulating valves.

- -Anti Seize and Anti Wear
- -Dirt repelling barrier dust-proof, anti-ash, anti-pollution
- -Can mix in other Jubricants



500ml







FUKKOL SPRAY GREASE

Ref:12281

Description

Rich high solid lubricant is a multifunctional lubricating grease spray made ofhigh viscosity lithium. It is simple and convenient to use. Rich high solidlubricants can provide a layer of excellent lubricating film and anticorrosion function. This product can be widely used in some movable guideways, bearings and other places.

Application

This heat-resisting lubricant grease is specially designed to dissolve to the gas form , so that it will have long term lubricating after highly penetrated into machine parts . It can apply to rotating parts , sliding parts and all bearings in all kind of machines

- -Excellent lubricating film
- -Good anti corrosion protection
- -Wide temperature range -15°C to+120°C
- -Uneasy to throw off when dripping
- -Can be used in severe duty, high temperatures and in the presence of moisture



500ml







HEAVY DUTY OPEN GEAR LUBE

Ref: 21145

Description

FUKKOL Heavy Duty Open Lube It is composed of inorganic non-soap-based thickener, graphite, high viscosity base oil and special additives.

Mainly used in low-speed heavy-duty super-large rotating equipment, High load per unit area of gear tooth surface. Linear contact of tooth surface. Prone to noise and vibration, Therefore, it is not only required that oil products have high load-carrying capacity, And the friction coefficient of friction pair should be reduced.

Application

Lubrication System for Open and Semi-closed Gear Box and Low Speed and Heavy Load Gear Devices, Widely used in cement, metallurgy, mining and other industries of operating machinery, Especially in some super large rotary equipment, such as ball mill, dryer, rotary kiln, etc.

- -Good adhesion and cohesion.
- -Excellent high temperature performance, using inorganic thickener with extremely high dropping point.
- -Excellent load-bearing capacity, using selected solid lubricants to ensure that it can maintainstable lubrication even under vibration loads.
- -It has high-quality graphite solid lubricant to fill dents and unevenness on the tooth surface; it always keeps its good properties in high and low temperature environment, does not dry and paint, andcan play a good lubrication and protection role on gears.
- -Completely free of solvents and heavy metals.



860ml







RUSTKING S TYPE

Description

High efficiency omnipotent antirust lubricants can be used to clean all kinds of metal devices, which caneasily remove the mud and hard material in the mechanical friction pairs, such as: in the gun barrel aftershooting, it can be sprayed or soaked after multi effect omnipotent antirust lubricants and then used forcleaning.

Ref: 16348

When the spark plug contact of the vehicle is defective, it can be sprayed with multi effect and all-purpose antirust lubricant without the need of erasing. It is very easy to start. Multi effect and all-purposeantirust lubricants can also be used to remove the tar and sticky adhesive stuck to the car table easily.

Thedried sugar on the carpet. Multi purpose omnipotent antirust lubricants antirust lubricants multi-purposemaintenance agents, with rust, dehumidification, rust, lubrication, cleaning, conductance of the six functions, and play a role.

The multi effect and omnipotent antirust lubricants can effectively maintain all kinds ofmechanical equipment, precision instruments, parts and components, and can keep the metal products ingood working condition for a long time and prolong the service life.

Application

1. multi effect omnipotent antirust lubricants can not stick to all kinds of precision metal devices, such as clocks, turret rollers, motor converter bearings, automatic weapons, drive chains, throttle control valves, connecting rod cable, motor drive grooves, motor shaft, pump shaft, rotary compass, control dashboard, air pressure and automatic control instrument. Doors and windows slide parts, door locks, door hinges, etc. Especially electronic plug-in, after the treatment of the multi effect and omnipotent antirust lubricant, the product lubrication period is greatly improved, the product competitiveness is increased, and the service life of the carbon brush is increased.

2. multi effect omnipotent antirust lubricants are suitable for long effect rust prevention of cast iron, cast steel and powder metallurgy parts. It is especially suitable for rust prevention of ship and metal parts. It is also suitable for electronic precision instruments, radar and gear, automatic weapons, turret roller, control panel, precision fittings, hardware tools and mechanical accessories. Mother machine, electrical contact point, bomb projection system, alloy jet turbine will be used for iron and steel parts, and can prevent high sensitive components from corrosion and oxidation.









FUKKOL ELECTRONIC CLEANER

Ref:77438

Description

High precision electronic cleaning agent is a kind of good quality cleaning agent for plastic and other substances; low and high solubility in surface tension, rapid volatilization and thorough, reduce the time of maintenance required for maintenance, chemical properties stable, non conductive and non corrosion, no CFC'S; can quickly remove all kinds of damage electronic instruments Contaminants.

Application

It can effectively remove grease and oxide from the circuit board or electrical components, and can be applied to the cleaning of transformers, telephone controllers, electronic instruments, computer equipment, circuit boards and electrical components.





Categorey Code:H1 NSF Registration No.159718

500ml







FOOD GRADE CLEANER

Ref: 11632

Description

pecially choose non-toxic and FDA compatible formula to remove all kinds of oil stains on machine parts, moulds and tools. The cleaning agent has strong cleaning ability and can penetrate quickly into all parts of the clear object.

Application

It is recommended to wipe out grease, fatlute, oil stain contamination of all kinds of metal surface of electronic parts, precision mirror moulds, tools, Food Machinery parts, etc.

Precautions

- -Shake well, hold upright and spray from a distance of approximately 20cm. One pass usually provides sufficient coating. Pressurised container, protect from sunlight, store at temperature below 50°C
- -Do not puncture or incinerate the can
- -Do not spray on to naked flame
- -Inflammable









MOULD CLEANER I

Ref:11166

Description

This precision electrical cleaning agent is a mildenvironmental friendly cleaning agent that does not damage plastics, has low flash point and does not contain CFC113 or three chloroethane. This product has a rapid volatilization

and can be widely used in clean and highly sensitive electronic equipment and equipment.

It can also be used in mechanical equipment and moulds. It can effectively remove all kinds of stains and keep the equipment stable. Regular

use of this product can be used for repair and maintenance, which greatly saves manpower and cost of replacement parts

Application

Can clean all precision electronic instruments and metal mold equipment, such as: contact, circuit floor, switch, telephone, PC component, motor (engine) relay, generator, magnetic head, current circuit breaker, plug and socket, electrical appliance, connector, electromechanical combination, laboratory instrument and so on.



500ml







MOULD CLEANER |

Ref:15548

Description

It does not contain CFC113 or three chloroethane. It has good stability, fast volatilization, no damage to plastic, and fast stain. It can clean all mechanical equipment, plastic or metal mold equipment, and all maintenance and cleaning of oil.

Application

Can clean all precision electronic instruments and metal mold equipment, such as: contact, circuit floor, switch, switch, telephone, PC component, motor (engine), relay, generator, magnetic head, current circuit breaker, plug and socket, electrical appliance, connector, electromechanical combination, laboratory instrument and so on.



500ml







GAS MARKS & GASKET REMOVER

Ref:66866

Description

The rich and high mold, gill stain cleaning agent is solvent type, high strength degreasing agent, effectively removes gasket rubber and gasket sealant.

It can dissolve or remove paint, varnish, adhesive and metal paint.

Application

Effective removal of motor, pump, flange basin and other gaskets, and can also remove paint. Adhesive, painting, removal of metal surface and stone surface.

- -It can quickly remove gaskets, plastic rings, locking glue and sealing rings.
- -Loose carbon residue can be loosened.
- -To protect the surface of the equipment by reducing excessive scraping.
- -Excellent paint scavenger
- -No dichloromethane



860ml







HEAVY DUTY DEGREASER

Ref: 51168

Description

The high and fast heavy duty scavenger is a kind of fast and effective removal of oil, asphalt, dirt, dirt, corrosion, sediment and other indomitable substances, and increase the operating efficiency of equipment.

It provides quick and effective degreasing, quick evaporation and no residue. Please be careful when using plastic.

Application

Generating units, engines, motors, gears, cables, electrical valves, mechanical transmissiondevices, etc.

- Non conductive, non corrosive, non contamination.
- High dielectric strength 37600 volts.
- High definition cleaning force129KB.
- No first / two ozone layer destruction.

Testing Series



Crack Test Complete Set







Intercheck[™] Cleaner

Ref:103058

Intercheck[™] Cleaner / remover are specially formulated to remove oil, grease, dirt and other most stubbom dirt from mechanical part, moulds and toolings.

Intercheck™ Cleaner are easy to apply and provide excellent cleaning power and instant penetration to hard reaching areas.

Intercheck[™] Penetrant

Ref:103059

Intercheck™ Penetrant is a general purpose water washable red colour contrast penetrant. Intercheck™ exhibits outstanding penetrating characteristics which provides for maximum reliability in locating surface-open flaws and discontinuities. Intercheck™ is formulated to give excellent controlled washability over a wide temperature range and variable dwell times.

Typical applications include castings, forgings, leak testing, welds and general metal work.

Intercheck[™] Developer

Ref:103060

Intercheck[™] Developer is a ready to use suspension of white developing particles in a fast drying solvent. Intercheck[™] Developer produces an opaque white coating, which provides an excellent contrasting background for Intercheck[™] penetrant indications.

Testing Series



500ml







LEAK DETECTOR SPRAY

Ref:103061

Description

High gas leak detection spray is a specially manufactured liquid. It is specially designed to measure extremely fine gas leaks. A thin, homogeneous film is formed after spraying the high gas leakage spray spray because the surface active additive can accurately point out any gas leakage or leakage at the joint.

Directions for Storage and Use

- Shake can well before use.
- -- Spray from a distance of 25 to 30 cm onto the area to be tested.
- Bubbles in the applied film indicate the location of a leak.
- Test compatibility with painted or coated surfaces, plastics and rubbers prior to application.

- FUKKOL Leak Detector Spray is suitable for use with most gases.
- FUKKOL Leak Detector Spray can be used with most types of refrigerant gases.
- The product has a low chlorine content ensuring maximum plastic compatibility.
- FUKKOL Leak Detector Spray is compatible with most metals and plastics.
- FUKKOL Leak Detector Spray is supplied in a convenient aerosol format to ensure consistent and accurate application.
- No wastage or spillage.

Spray Paint Series



450ml







COPPER CORROSIVE INHIBITION SPRAY PAINT

Ref: 91193

Copper-coating is for different applications. Application: To coat different material, I.e. metal, plastics, glass, wood, etc., to adjust different material to nearby copper-surfaces and also for repair of existing copper-surfaces, e. g. to overcate tin-seams; for arts and crafts and hobbies.

Use: Shake can well and spray onto clean surfaces. Properties: Highly refined copper (purity 99.9%), the dried film has a high copper content, mechanical resistance is thus reduced, the copper-coating will be tarnishing(patina) and adjusting to existing copper-surfaces, e. g. window-sills etc., within half a year to a year, conductivity will be disappearing within half a year, fast drying: dust dry within approx. 4 to 6 min., dry to handle within approx. 8 to 10 min. (at normal conditions, i.e ambient temperature, etc.), copper hinders the growth of algae, etc., self-cleaning valve-do not purge after use.

BRASS CORROSIVE INHIBITION SPRAY PAINT

Ref: 91294

Brass Spray is a metallic coating with a high brass content and a colour shade typical of brass. For the protection and optical refinement of various materials. Properties the dried film has a high brass content mechanical resistance is thus reduced the brass-coating will be tarnished ("patina") and adjusting to aged material within half a year to a year drying time: dust dry within approx 6 to 9 min.* dry to handle within approx 14 to 20 min.* (*at normal conditions, I.e. ambient tem-perature, etc.) self-cleaning valve-do not purge after use.

Spray Paint Series



450ml







ALUMINUM CORROSIVE INHIBITION SPRAY PAINT

Ref: 91395

Liquid Aluminum Spray is abrasion-proof, resistant to many dilutedacids and lyes, as well as to atmospheric influences. It containsaluminium pigments with a purity grade of >99.5%. Application Specially for surfaces which can get hot, for instance inincineration plants (garbage/refuse/water), boiler and combustion plants, long-distance heating works and pipelines, furnace equipment, e.g. gateand other valves, sheets of catalytic converters, exhaust manifolds.

silencers, exhaust pipes of cars and ovens, for "gliding" purposes in continuous aluminium-casting (spray form with Liquid Aluminium Spray instead of graphite, the latter gives a "dirty" alu-surface) and for all hard surfaces not subjected to abrasion, e.g. metal, wood, ceramics, etc., for air-conditioning/ventilation systems, silos, road truck body work, alu wheelrims/felloes, for touching-up fresh zinc-coatings. etc.

STAINSTEEL CORROSIVE INHIBITION SPRAY PAINT

Ref:91496

Fukkol Stainless Steel Spray "bright grade" is a chemical, corrosion and weather resistant surface coating on the basis of acrylic resin and stainless steel pigments. It is temperature resistant up to +300°C for short periods and provides a treated stainless steel look. Stainless Steel Spray "bright grade" can be used wherever a resistant and effective protective layer is required.

The alloy is comprised of e.g. chromium, nickel and manganese. Fukkol Stainless Steel Spray 'bright grade" can be used to repair damaged stainless steel parts on truck bodies, silos and pipelines, and in outdoor applications. It can also be used for decorative purposes and for the optical refinement of glass, wood, stone, ceramics and most plastics.

Spray Paint Series



500ml







HIGH HEAT ANTI CORROSIVE CONDUCTIVE

Ref: 91697

Description

FUKKOL High Heat Anti Corrosive Conductive mixture of superfine flake graphite as solid dispersionphase, organic solvent and organic binder is prepared.

Colloidal graphite with high purity, fineparticle size, good dispersibility and chemical stability with fixed carbon content of 95% or moreWas used. The paint film formed after drying can play a conductive role, thus shielding theelectromagnetic interference function.

Application

Electronic, electrical, aviation, chemical, printing and other civil industrial fields have been applied.

- 1.Excellent adhesion and impact resistance.
- 2. Conductive heat dissipation is stable.
- 3.Excellent water resistance, salt water resistance and chemical corrosion resistance.
- 4.It has good temperature resistance and can withstand the alternating impact of heat and cold.

Spray Paint Series



500ml







ZINC COLD GALVANIC SPRAY

Ref: 91596

Description

FUKKOL Zinc Cold Galvanic Spray A single component anti-rust cold galvanized coating capable of joining with any metal substrate. High performance zinc plating agent with 98% pure zinc content in thin films, It can be adhered to bare metal by electrochemical action.

This coating provides active plating protection, Rust can be prevented even in case of scratches or wear. The coating dries quickly and has excellent adhesion. Grey coating is formed after use.

Application

Protect and repair galvanized sheets, structural steels, steel roofs, doors and windows, marine equipment seriously corroded by sea water, public equipment, metallurgical plants, water treatmentplants, paper mills and other facilities.

It can also be used to repair galvanized parts, such ascutting surface, welding seam and parts that are difficult to repair by hot galvanizing.

Benefits

- 1.Excellent adhesion, impact resistance and flexibility.
- 2. Excellent weather resistance and color and light retention.
- 3. Super anti-aging and anti-corrosion properties.
- 4.Excellent water resistance, salt water resistance and chemical corrosion resistance.
- 5.Excellent temperature resistance, can withstand cold and hot alternating impact.



Hand Torch and MAPP Gas Sets



1000ML

HT MAPP GAS

Ref:100025

Description

Work faster and more efficiently with a higher burn temperature than standard propane.

The FUKKOL HT MAPP Gas Hand Torch Cylinder contains premium fuel suited for a variety of job site projects including soldering large copper pipes, brazing and heat treating. Constructed of durable steel, the slim, lightweight cylinder is easy to grip and maneuver. Flame temperature in air is 3, 730 degress Fahrenheit.

Benefits

- 1.Use with hand torches designed for MAP-Pro fuel, including Bernzomatic torches
- 2. Flame temperature in air of 3,730 $^{\circ}$ $\,$ F / 2054.4 $\,$ C, ideal for medium to heavy soldering and brazing
- 3. Faster heat transfer than propane fuel
- 4.Slim, lightweight cylinder is easy to grip and maneuver
- 5. Durable steel construction
- 6.TL-18 Connection

HAND TORCH TL-18

Ref:100024

Description

Work faster and more efficiently with the versatile High Heat Torch for Fast Work Times, designed for a wide range of jobs including soldering large diameter copper pipes, brazing and heat treating.

The optimized swirl flame burns hot and fast soldering times. The auto start/stop ignition lights and extinguishes with the push of a button, run-lock button keeps torch lit for continuous use.





MAPP/OXYGEN Quick Cut Welding Kit

Ref:120026 100030

Description

EXTREMELY FLAMMABLE GASES USEDTORCH. FIRE/EXPLOSION HAZARD.CARBONMONOXIDE HAZARD

This oxygen brazing andcutting torch is unlike most hand held torches. It is designed to be used simultaneously with anoxygen cylinder and a MAP-Pro Gamma or propanecylinder. The use of an oxygen cylinder results inthe torch flame burning at much highertemperatures as it would without an oxygencylinder.

Do not use this torch until you becomethoroughly familiar with its proper use and potential hazards. In particular, you must notattempt to ignite the torch while oxygen is flowing to the torch. Further, when turning the torch off ALWAYS TURN OFF THE OXYGEN BEFORE TURNING OFF THE FUEL GAS.

Turning off the fuel gas while oxygen is still flowing could result in a flash back and an explosion.

Method of application

- 1.Before attaching the hoses to the cylinders, make sure the oxygen and the fuel valves on the hoses are OFF by turning the knobs clockwise until the knobs stop. Hand tighten only. Do not force.
- 2. Thread the fuel cylinder clockwise onto the fuel hose valve (1). Hand tighten only. Do not force.
- 3. Thread the oxygen cylinder counter-clockwise onto the oxygen hose valve (2). Hand tighten only. Do not force.
- 4. Place the cylinders, while attached to the hoses, into the stand (3). Do not attempt to ignite or use the torch unless the cylinders are secured in the stand.
- 5. Place the cylinder stand on a stable and level surface. Improper stand position, such as placing the stand on its side, could cause accidental tip over leading to liquid fuel entering the hoses and causing excessively long flame or flame outage.



500ml

FOOD GRADE BELT

DRESSING SPRAY

Ref:55455

Description

Belt Dressing is formulated to extend belt life, prevent belt slippage, and resist water wash out.

Benefits

- Prevents belt slippage on at, round, and V-belts
- Eliminates squeaks from slipping belts
- Water resistant
- Extends belt life and pulley bearing life
- Does not contain chlorinated solvents that deteriorate drive belts
- Metal detectable plastic components (see back for more details)
- May be used in wet, outdoor conditions
- ■PONY® certificate registered.

How to Use

- 1. Shake aerosol well before use.
- 2. Apply from a distance of 15-30 cm (6-12 inches).
- 3.For best results apply a thin film directly onto the drive face of the belt.
- 4. Ensure adequate ventilation during use.
- 5. Test compatibility with plastics and rubbers and
- 6. painted or coated surfaces prior to application
- 7. The storage temperature should be kept below $+50^{\circ}\,$ C, and the storage area should be out of direct sunlight.

Engineering Chemicals



WELDING HEAT RESISTANT COMPOUND

Ref:100026

Description

FUKKOL Welding Heat Resistant Compound It is an insulating paste made of ceramic matrix and variousinsulating materials. It can withstand high temperature of 4000°C.

It can prevent heat transfer ofwelding and brazing up to 4000°C in millimeter range, prevent coating from burning and avoidtime-consuming disassembly process.

Benefits

Fusion welding and brazing of pipes, chassis, metal sheets, such as welding of thermal sensitive components such as aircraft wings, electronic circuit boards, etc.

How to Use

- 1. Reusable ceramic thermal protection paste, suitable for heat insulation of fusion welding and alloy welding.
- 2.No thermal damage will occur on the surface of workpiece to avoid distortion, warping and distortion, of thin plate during welding.
- 3.It can prevent heat transfer of soldering and lead-tin soldering at temperatures up to 4000°C in millimeter range.
- 4.lt also provides higher safety protection, such as in the vicinity of oil and fuel pipelines.
- 5. There is no need to disassemble and reassemble heat-sensitive components, no burning of cables and insulating layers, no unnecessary decomposition, no impact on coatings, no damage to chromium-plated layers and plastic surfaces.

Welding and Cutting Series



500ml

WELDING ANTI SPATTER SPRAY

Ref:63118

Description

Prevents spatter from adhering to surrounding metal surfaces during welding. Water-based formula allows easy clean-up without the use of solvent cleaners.

Benefits

- Unique water-based formula
- prevents weld spatter from sticking to metal
- Biodegradable
- Non-toxic, non-flammable
- Aerosol hasanoversized, Spray Nozzle that is ideal when wearing welding gloves
- Does not contain chlorinated solvents
- Does not contain silicone
- Paint compatible
- Eliminates the need for chiseling, grinding, or brushing after welding
- Acceptable for use in Food Processing Establishments.

How to Use

- 1. Surfaces to be coated need to be cleaned and degreased.
- 2. Shake can for at least 1 minute to homogenize before use.
- 3. Spray from a distance of about 10 to 15 cm. Apply sparingly as excessive coating thickness causes flaking off.
- 4. When applying SF 7900 Ceramic Shield to the tip of a plasma torch / cutter, ensure the air purge is on during application to prevent the product from clogging the tiny holes around the center orifice.
- 5. Allow product to dry.
- The translucent film becomes white upon evaporation of solvents.



TOWER MAINTAIN B Ref: 100323

As to water tower, the usual problems lie in the rust in circulating system, microbe and bacteria growing in the water which may agglomerate and adhere around the venturi and the channel as a block to make the circulating system abnormal and lack of heat dissipation. As a result, the water temperature will rise and the tower will lose cooling function, thus, more heavy maintenance will be required.

Maintenance

Actually, tower maintenance will become very easy after the above problems are resolved, no need professional skills.

Currently, our company provides two kinds of maintaining products, economic and effective, specially designed for maintaining tower cooling system so as to prolong the life of the water tower system.

Application method

No matter the tower is old or new, just add the (A) cleanser in certain amount according to the Cleanser Proportion Table to the water and make the water circulate for one day, and then discharge the used water, and add clean water.

Add (B) protective agent in certain amount according to the Cleanser Proportion Table to the water for heat dissipation. Thereafter, it is only required to add (B) protective agent for heat dissipation every four to seven months to get the tower perfect maintenance for a long time.

FUNGICIDE Ref:100326

FUKKOL Fungicide can be used with all types of water mix metalworking fluids. It is formulated to eliminate fungus and prevent the formation of fungal growths which can cause blockages and lead to costly downtime.



BACTERICIDE Ref:100325

FUKKOL Bactericide is a nitrite - free medium to heavy duty machine, tool cleaner and steriliser, based upon a powerful detergent. It has been specifically formulated to deal with a wide variety of machine tool contaminants and is easy to use with minimum disruption to production, being added direct to the coolant system whilst still in operation. Not applicable to neat oil system.

AIR CONDITION

Ref: 100385

RADIATOR CLEANER

FD-24 Air Conditioning Coils Cleaner is a viscous liquid which has been formulated specifically for cleaning and brightening stainless steel and aluminum trim, window frames, storm windows, screening and air conditioning coils. The product will not erch glass, so no masking is necessary.

FUSICLEAN

Ref:100324

FUSICLEAN SYSTEM CLEANER

FUKKOL Fusiclean System Cleanser is a nitrite free medium to heavy duty machine, tool cleaner and steriliser, based upon a powerful detergent. It has been specifically formulated to deal with a wide variety of machine tool contaminants and is easy to use with minimum disruption to production, being added direct to the coolant system whilst still in operation. Not applicable to neat oil system.

ANTI FOAM X Re

Ref:100518

FUKKOL Anti Foam X is modified dimethyl siloxane with the characteristics of non-volatile, non-toxic, odorless. It is milk white liquid and insoluble in water. It can be dissolving in organic solvent, such as aliphatic hydrocarbon, with well heat stability(stable under 200°C). It has well antifoaming effect with little dosage.

TOWER CLEAN A Ref:100322

Tower Clean A is an acidic liquid which can be used to remove special water scales such as water scale, oxides, etc., without etching any metal materials in acid cleaning.

Tower Clean A is specially used to eliminate the special water scales in circulating cooling system, heat exchange system, condensator, etc.

PAINTO LIC PAINT REMOVER

Ref:100079

Description

Painto Lic is soaked at normal temperature for use, which is convenient, incombustible, with fast depainting speed, widely used in metal painting layers to prevent the metal surface from any corrosion, discoloration, etc. when the paint layer on the metal surface is removed.

Application method

Soak the workpiece in the paint remover, and after the paint film is removed, take out the workpiece, make it clean and dry using pot scourer or towel.

The soaking time is determined as per the paint thickness. As to the initial application or no experience in such application, it is recommended to make trial application first with a small amount, and then make application with a large amount.

Attention

*This product has slight irritant action and certain toxicity, labour protection appliance (including gloves and gauze masks) is required in operation.

*Keep child away from the product and NO drinking.

*Keep the product in a cool and well-ventilated place; make eye-catching marks such as "hazard! Don't touch!" and Don't expose the product in the sun.

MIKI WAX 100

Ref: 100352

MIKI Wax 100 is made from advanced cleaning formula, it may clean efficiently dust, scales and dirty from wood floor and wood furniture. With special additive to keep furniture clean and a good condition when use it often.

WAX REMOVER

Ref:120353

Description

The wax remover is refined from the imported surfactant which has strong degreasing action, effective accessory ingredient, etc., having advantages of fast, thorough and enduring wax removing, oil removing without damaging the substrate, long service life, nontoxicity and low foam, being biological degradated thoroughly, etc.

Application method: ultrasonic cleaning steps: for solution preparation, it is required ti add the water into a clean trough; when the water is heated to 60°C, add wax remover slowly while stirring and stir the solution sufficiently and evemly; and finally heat it to the required temperature for use.

EXTERAL WALL POWER CLEANER Ref: 1100372

FUKKOL EXTERNAL WALL CLEANER Concrete Cleaner is specially formulated to remove common construction and atmospheric staining from a variety of substrates, including smooth architectural and engineered concrete, custom masonry, concrete brick, manufactured stone and decorative payers.

This general-purpose, non etching acidic cleaner removes rust, mud, atmospheric dirt, mortar smears and other stains without altering the surface texture. Light Duty Concrete Cleaner adds depth to colors, broghtens white matrices and exposed aggregate.



Metal polish

METAL POLISH COMPOUND OXCIDE REMOVE

Ref:120132

Metal Polish Compound Oxcide Remove is ideal for quickly cleaning your wood f uruiture and wood surfaces.

Its Anti-Dust formula keeps surffaces looking less duusty, longer.

It removes dust, dirt, smudges, and common allergens like pet dander found in dust from your wood furniture in a flash. Plus, it protects against water damage and stains. Dusting with Pledge leaves surfaces with no waxy buildup.



STICKER REMOVER

Ref: 100329

Description

FUKKOL Sticker Remover CPS is designed for removing problem of stickers. It leaves no sticky residue, harms no work-piece and affects no any work processing.

Benefits

- 1, Do not apply to food.
- 2, Long time skin contact may cause dry skin.
- 3, Use it in ventilated place.
- 4, Keep away from source of ignition.



SUPER GLUE REMOVER

Ref:100516

Description

SUPER GLUE REMOVER may be applied directly to the cured adhesive surface and does not run or migrate. Allow sufficient time to penetrate and then begin rubbing, brushing, or sanding off softened adhesive layers. Several applications may be required to remove thick deposits of the adhesive.

The parts may be soaked in the SUPER GLUE REMOVER as an alternative method. Always use SUPER GLUE REMOVER in a well-ventilated area.



80ml

PHLADO ANTI-STATIC AGENT

Ref: 56397

Description

PHLADO is a surface-active product that PHLADO can effectively dissipate the static electricity cased by friction. When sprayed, PHLADO forms an ultra-thin invisible film on the surface and prevents further accumulation of static charges.

Reliably gets rid of static-charge from production lines of plastic products & synthetic fibres; plastic surfaces, textiles made of synthetic fibres, fitted carpets, acrylic walls, glass, screens, TV-housings, furniture, seat cover, etc. PHLADO can prevent false mater readings by eliminating the static charge around the instruments.

Benefits

- Does not affect most coatings, rubbers and plastics.
- Simple and effective
- · Excellent anti-static effect.

Cautions

Flammable, use with adequate ventilation. Use only as directed. In case of eye contact, flush with water for 15 minutus. If swallowed, do not indue vomiting. Keep out of reach of children. Connects under pressure, do not puncture, incinerate or store above 120°F(49°C). Keep in a cool place.



ALU CLEANER

Ref:100378

FOKKOL Alu CLEANER is silumin acid de-oil washing white agent used in room temperature. It is make up of various composite acid, emulsify, disperse and cleaning material.

FOLLOL ALU CLEANER can remove the oxide on the silumin surface after sialsphere die-casting and sandblast-ing with dipping and ultrasonic. It can make a great smooth finish surface after stoving and will not have effect on the processing place's (drill, CNC turning) smooth finish.

ALU PROTECTOR

Ref:100379

FOKKOL Alu PROTECTOR is an oil soluble and water dispersion negative negative ion liquid or colloidal solid inhibition, rust corrosion problems, and free from silicate and phosphorus.

FUKKOL ALU PROTECTOR is designed with unique technology of aluminum alloy corrosion inhition, and have great emulsifying and lubricating properties.

FLOOR POWERFUL CLEANER

Ref:100373

FOKKOL FLOOR HEAVY DUTY CLEANER is a concentrated liquid blend of alkaline materials, surfactants and emulsifiers which will transform deposits into the form of a fine emulsion. easily dispersible in water.

This new product is formulated to combine safe and effective features.

Metal Degrease



AUTO CLEANER

Ref:100380

FOKKOL AUTO CLEANER is a professional copper equipment cleaner with organic acid and active agent formula, which is designed for copper material and will not have electrochemical corrosion to copper. It is a quick and safe cleaner to copper equipment, which is mainly used in condenser and evaporimeter heat exchange equipment cleaning.

FUKKOL AUTO CLEANER is characterized with corrosive same, room temperature cleaning capable and quick cleaning speed.

COPPERLEX

Ref:100381

FOKKOL COPPERLEX is a corrosion inhibitor specialized desighed gor copper and copper alloy. It is formed by varioue corrosion inhibitors and corrosion inhibitor potentiating agent. It has excellent corrosion inhibition properties. FUKKOL COPPERLEX suitable for copper anti-corrosion, which can form a thin and

compact corrosion prevention film quickly on the surface of the copper material.

The film can protect the copper and material free from air and deleterious mediums corrosion. It features with film forming quickly and excellent Fill membrane effect, but have corrosion inhibition effect on metals such as: carbon steel, aluminum, nickel etc. FUKKOL COPPERLEX can use with many kinds of antisludging agent and Biocide in circulating cooling water system.

ULTRASONIC DETERGENT

Ref:100367

FOKKOL Uitrasonic Detergent is a highly concentrated, aluminum safe-multi metal, Liquid Alkaline Detergent engineered s for the ultrasonic cleaning of the toughest contaminates on all metal.

Specially in bicycle chain deep clean and oil remove.



RUST REMOVER

DAC 2

Ref:100078

Description

Fukkol DAC2 is a special viscous liquid ac -id formulation having a special cationic type penetrant and stable inhibitor which provides effective protection on most metals and many other surfaces. It can be used in ways like dipping, brushing or wiping, etc.

Application

Ideal for prepaint treatment of metal surfac-es, finishing housing and panels, aluminum and tin boilers and molds, brightening aluminum and stainless steel. Also applicable for cleaning radioactive contaminated equipment, cleaning tile and grouting.

Benefits

DAC 2 has rapid wetting and penetrating ability, thus providing faster rust and corrosio -n removal than other commonly used acids. Effective in a wide range of temperatures DAC 2 special inhibitor does not precipitate out and become inactive even after large amo -unts of rust and corrosion have been dissol -ved . DAC 2 rinses freely and contains no muriatic acid.

500ml

Heavy Duty Stain Cleaner

Ref: CL-FU-4442

Description

CLEANOLOGY HEAVY DUTY STAIN CLEANER is pros knowthat acids required to remove calcium, lime scale and rust. This professional grade concentrated acidic solution brakesup deposis quicks, removing stain & buildup that other cleanercan't.

CLEANOLOGY HEAVY DUTY STAIN CLEANER is apleasantly scented, all-puropse cleaner designed for the rapidremoval of grime, lime, rust and other heavy soils. It instantly penetrate greasy and oily surfaces, providing powerful emulsifying ingredients that chemically soften and disslove the deposits, making them easy to remove. A safer, effective, alternative to toxic cleaners, bleaches and solvents! CLEANOLOGY HEAVY DUTY STAIN CLEANER is econmical. The CLEANOLOGY HEAVY DUTY STAINCLEANER quart comes with a versatile sprayer applicator.



Application

- ■Pre-Cast Concrete Paver
- ■Masonry
- ■Flamed & Honed Granite
- ■Flamed & Honed Limestone
- ■Quarry Tile
- ■Fountains

MACHINERY POWERFUL DETERGENT Ref:10

Ref:100364

Description

Machine Powerful Detergent is an emulsifiable machine degreaser and detergent that is suitable for use in self-contained and centralized systems.

This product has been specifically developed for the machining industry, to ensure cleanliness and sterility of soluble oil emulsions in service.

Machine Powerful Detergent is also recommended for use when cleaning machines prior to refilling or top up. Machine Powerful Detergent provides a degreasing and disinfecting action in one complete cleaner.

Benefits

- neutralizes bacterial infections
- attacks and removes fungal growths
- ensures pleasant odors effectively removes oil and slime
- reduces down time costs

How to use

Dillute with hot or cold water (ratio:1-2%)in circulating system for 24-48 hours, or directly use it or by spray. Wear glove and mouth muffle before use.

GUMICE DISINFECTING

HAND CLEANER

Ref: 100370

Description

Pumince Hand Cleaner is natural, biode gradble hand cleanser petroleum solvents. It cleans hands with d-Limonene, a solvent extracted from oranges.

This hand cleaner has a fresh citrus scent and contains no artificial fragrances. Both the cream and lotion formulas are available in smooth or pumice. Pumice Hand Cleaner contains aloe vera, lanolin, glycerine and jojoba oil for skin conditioning.

Benefits

- 1. Effective removal of grease and dirt.
- 2.It can be washed without water.
- 3. Containing biodegradable surfactants.
- 4.Non blocking drains and automatic hand washing machines.
- 5. Contains aloe vera, lanolin, glycerin and jojoba oil.
- 6.Pleasant smell.
- 7. More smooth after use, effectively removing dirt in gaps.

How to use

- 1.Rub hand cleaner into hands (do not use water) until dirt and grease is dissolved.
- 2. Wipe with dry cloth or rinse with water.



Adhesive Series



Adhesive Series

THREAD LOCKING ADHESIVES

Thread

Ref:100334-609 100335-242 100335-271 100334-638 100335-262 100335-222



Androgynous thread locking adhesive. Solidifying under the oxygen-free condition. Easy to remove and antivibration.

Applicable to frequently replaced parts such as tiny screws and brass products, but not to plastics.





Mid-strength, dismountable parts are easy to assemble after lubricating. It cannot flow, drop and move after solidifying. with the characteristics of sealing and antivibration. Allowing controllable

pressure of torque for eas dismountin.



Red high-streng adhesive. Bearable to vibration, shaking and pressure.

Applicable in the heavy industry and bolts in the rail and engineering vehicles.



Low viscosity, quick bonding, **Pipeline** fast setting and mid-strength.

> Applicable to compact devices with small-gap and cylindrical parts, ideal for housing screws. Capillary action allows the products to wick into pin porosities, micropores and hairline cracks, reliably sealing diecast housings and welding sems.





High-strength permanent adhesive-sealant.Resistible.

Applicable in properly installed parts not necessary to frequently dismount, such as in screwing and assembling. High viscosity provides

additional gap filling properties. Depending on thread diameter, breakout or removal is difficult to ineffective.



Mid-strength and viscosity. Applicable to keys, pinion racks and bearings, but not to compact codes.

Ref:100341-5352 100342-5354 UV-CURING ADHESIVES 100341-5353 100342-5355



Low-viscosity, high-strength, harmless, offering dry and flexible surface after solidifying.

Applicable in binding metals. metal with glass, metal with aluminum, especially in assembling of medical devices.




Excellent strengths of compression and shear, glass/glass(up to 26n/mm), suitable for two-stage solidifying, parts quick fixing(10S), thoroughly dried by the UV lamp lighting for the second time after cleaning the residual adhesive.



Low-viscosity, applicable in binding with quick solidifying and very high strength, high chemical resistance.

But not applicable in binding in the environment of pure oxygen and pure chlorine. Mainly in glass decorations, watch surfaces and jewelry.



Applicable in medical equipments.

101

Adhesive Series









Multi-puropose adhesive

Ref: 33443

Description

This product is a kind of super performance adhesive. It can be widely used in the fields of Arts and crafts making, chartprinting or net plate printing, and sign making.

In addition, it is often used in the fields such as book mounting, knittingindustry, carpenter, etc., this product is not wrinkled, waterproof, can be changed from new transposition, fast drying andcan keep a long time.

A solid binder, which can be used for temporary or permanent bonding. This product can be widelyused in metal, cardboard, foam rubber, plastic film, glass, wood, paper and clothing. In any case, this product canproduce a layer of pressure sensitive film, in the screen printing, the T-shirt and other textiles can be adhered to color.

Application

- It can be used for studio, printing, picture mounting, screen printing, signs, signage production, sewing, woodworking, office and workplaces.
- It prevents the parent manuscript and the plate from shifting.
- It can be used for fast and high viscosity temporary or permanent adhesives.
- Without wrinkle, it can be repositioned, waterproof and stain free. It is ideal for ideal quick layout or paste.

Benefits

- 1. The adhesive force is very strong, fast and easy to use.
- 2.the adhesive concentration is high, spraying glue covers a large area, is 1.5 times to 2 times the same kind of glue spray.
- 3.spray particles are fine and uniform, low permeability and easy to corrode the base material, and save viscose.
- 4. with 5-10 minutes to fit the lead time, enhance work flexibility, improve work efficiency.
- 5.wide range of applications, suitable for factories, companies and families to use.
- 6.It has a revolving 360 nozzle, which is convenient to use.

Instant Adhesives & Clay

FAST CURE ADHESIVES

Ref:100348

100349 100350



Instant glue 838 is applicable to bind rough, porous and acid material including labeling wood, board, plywood, rubber, cork and leather.

100348

HX 838



Instant glue 848 with low bloom is designed speciall to bind cosmetics packages, so the bound spot does not whiten and yellow even in the poor ventilating circumstances.

100349

HX 848

Instant glue GA-40 is designed for materials hard to bind, such as rubber, plastic, metal and other materials, especially for PVC, ABS, nvlon, fluorocarbon. 100350


GA-40

Ref:100355-5min

100356-30min 5/30 MINTUTES EPOXY ADHESIVE

Permatex PermaPoxy products are two part, clear epoxy adhesive systems. PermaPoxy Clear General Purpose epoxies are of a maximum strength formula that is available in several working times.

PermaPoxy is ideal for complex, multi-piece assemblies. They are water and solvent resistant and available in dual syringes or tubes.



It is designed of naturally polymer base and non toxic formula can be using again many time.

STICKEASY particular effective for remove the oily and carbon in precise parts. PC board, watch or non conductive cleaning. also using in machine sealant.



Repair Clay

REPAIR CLAY Ref: 100351

Easy to use

The 'white' and the 'vellow' substances should be worked together in a ratio of 1:1 until the resulting substance is totally 'grey' in colour. Apply within 15 minutes.

The area to be repaired must be clean, I.e. free from grease, rust, dirt, silicone, oil, etc.

When apply to smooth surfaces, make it lightly abraded before applying.

Universal application

META-FILL works perfectly on metals, wood, stone, ceramics, plastics and glass. Can also be used and applied underwater.

Easy to work on

Within 3 hours, META-FILL will be as hard as rock and can then be sanded, deilled, filed, sawn and threaded.

Repairs effected by META-FILL can be improved cosmetically by using a Metaflux Metal Spray or painted over.

Examples of usage

Insulation of pipes and tanks, securing of screws and hooks, renewing of taps, filling of uneven surfaces and holes and a for thousands of other uses.

Technical data

Heat tolerance:Up to 200°C Pressure resistance:8000 N/cm² Tensile strength: 3000 N/cm² Hardening:3 hours at 20°C Preparation time: 15 minutes Specific gravity: 2.0 Shelf life:At least 3 years if kept in closed container







Additives

H.T.M ELASTICIZER

Ref:100327

Description

1.H.T.M was based on special chemical additives. The medium viscosity is designed with new and recycle plastic material to improved. The surface reflet and toughen, and also provides stability with material. 2.H.T.M can be used in almost all kinds of plastic that is compliance with ETV and ASTM norms. It reach safety standard and can widely apply to toys, electrical equipments and household articles with no side effects.

Benefits

- *Non-Toxic and safety formulated.
- *Non-impact plastic material, add to stability.
- *Add to surface reflect with double shine.
- *Add to toughen ,it can take the place of impact resistance materical in some condition to decrease costing.

FLEXIBLE PLASTIC

MOULD RELEASE AGENTS Ref: 11338

Flexible Plastic Mould Release Agents is a 50% wt. aqueous emulsion of polyalkyl, alkarylsiloxane, it provids a durable parting film which effectively releases plastics, adhesives, and other elastomeric products that are sometimes difficult to release from mold surfaces, even with other silicones.



DIFFUSION OIL

Ref:100330

FUKKOL DIFFUSION OIL is used in the production for all kinds of plastic casting and agglomerates in result of several functions with the products, which improves greatly the product quality.

- 1.enhance the pigment dispersibility in result of the color uniformity and brighter.
- 2.make the ware with the brightness.
- 3.Lower the melt viscosity on surface, twist distance and extruded pressure of the machine.
- 4.Reduce and eliminate material deposits from the mouth mould and the melt cracked.
- 5.As the isolated reagent between the inner and the outer mould.

FOOD GRADE DIFFUSION OIL

Ref:100331

The rich high toner dispersing oil has been used in various plastics injection molding and masterbatch production, and gives many functions

to the products, which can greatly improve the quality of products.

Reference component: 25KG

ABS	P.P	PE,PVC	P.C	HIPS,GPPS	PET,PBT	PMMA,K-RESIN
30-40M	IL 25-30ML	25-30ML	30ML	25-30ML	20-25ML	25-30ML

INJECTION PLASTIC MACHINE SCREW CLEANER 官高株式會

Injection Plastic Machine Screw Cleaner

SCREW ROD CLEANING AGENT

O.T.C

Ref:13342

The special cleaning formulated is doing with forth method to have a forth extrude through the barrel of the injection moulding and extruder, excellent for color changes, resin changes, preventative machine maintenance, much advanced than before manual cleaning.

SCREW ROD CLEAR POWDER

O.T.S

Ref:100083

The cleaner powder for barrel of plastics injection molding machine is specially designed for cleaning screws and barrels by economic principles.

The product is made from inorganic compounds, which is white powder in physical form and has better effects to clean off deep colors like black and fluorescence color. Only 50g cleaner powder and 2kg plastics are required ti clean to plastics injection molding machines with 100 tons of clamping force once for changing colors.

SCREW ROD CLEAN RESIN

M.T.C

Ref:100082

It is a super compound, with characteristics that are not found in any other purging material and facilitate the molding industry trend toward small-lot multiproduct operations.

It combines efficiency and easy of use with outstanding cleaning power in purging injection molding machines and extruders for resin type or color interchange and for deposit removal.

SCREW ROD CLEANING RESIN

E.T.C

Ref:100086

For High Temperature 310°C-391°C Resin

FUKKOL E. T. C is a high heat-resistant, non-abrasive, non-chemical 'engineered' thermoplastic purging compound, formulated to purge high-temperature engineering resins.

A non-melting but softening thermoplastic scrubs the screw and barrel of both injection molding machines and extruders, while the carrier matrix flushes away impurities.

WATER RESISTANT OIL Ref:120309-I

II.II.II

FUKKOL Water Resistant series is a high-purity organic oil, it has a smooth structure and is extremely colorless. No effect to most rubber and plastic parts, resisting water washout and spray off, it provides excellent compressibility, making it for diving manchine and watchs

I:5-20ATM II:20-30ATM III:30-50ATM

TITANIUM AND STAINLESS STEEL WATCH PROTECT PASTE

Ref: 120157

Titanium paste with special protective agent is a special protective agent for watchcase and watchband after the production of clocks and watches. It especially prevents oxidation of hand sweat and improves surfacegloss.

PEELABLE PROTECTINE

Ref:84668-150G FILM COATING

FUKKOL Peelable Protective Film Coating is a rust and stain protection product that can be 'peel off when necessary'. It is suitable for metal mold, plating surface of mechanical product or polished surface with anti-rust, scratch and stain proof effects.

When the spray dried, it will form a blue or translucent film that has strong toughness and easy to peel off when don't need it. When peel off, the item under it will be as good as new. The formulations containing gasification rust inhibitor, this can help to release antirust ingredient to fill in packing voids and provides excellent anti-corrosion effect.

AL 5105 WATCH SPRING BAR **REMOVABLE SOLVENT 100%**

Ref:100318

The high concentration formula is specially designed for protection to the high requirement of horologe ass-emble. AL 5105 can be use in severe condition. AL 5105 can be dilute with alkanes solvent



Watch Assemble Series

WATCH SPRING BAR REMOVABLE SOLVENT

High FT-2 is lubricating solvent containing environmental extremepressure agent. Unique extreme pressure agent can make it lubricate inthe surface hole without leaving any substance. It is meeting therequirements of the clock factory.

The appearance of high FT-2 is not onlytransparent, but also can be accelerated by rapid evaporation. If the concentration is high, trichloroethylene can also be used to dilute it

WATER RESISTANT OIL

Ref:100311

This FUKKOL watch oil is a general purpose oil great for chronometers and wrist watches, up to size 18 Ligne.

This oil gives watchmakers an outstanding lubrication with minimal need to spread it at a low freezing point.

BLUE LUBE ONOMETER WATCH OIL

Ref:100312

FUKKOL BLUE LUBE ONOMETER WATCH OIL It is a kind of speciallubricating solvent for synthetic oil extreme pressure agent.

The unique extreme pressure agent can provide a kind of lubrication in the watch hole, which is meeting the requirements of the clock factory.



100311



Description

FUKKOL Formula Secret Engine Treatment is formulated with FUKKOL Formula Secret Engine Treatment AFMT advanced technology to treat the metal surfaces of both gasoline and diesel fueled engines. As motor oil is pumped through the engine, FUKKOL Formula Secret Engine Treatment molecules interact with all of the metal surfaces, chemically bonding to create a protective layer that reduces damaging friction and heat. Temperature reduction is especially important in today's smaller import and compact engines that tend to run hotter.

FUKKOL Engine Treatment is particularly effective under extreme pressure conditions, in the very areas of your engine where severe metal-to-metal contact squeezes motor oil out and away.

FUKKOL Formula Secret Engine Treatment adheres to metal surfaces in the engine, which means Fukkol Formula Secret Engine Treatment is working to protect your engine even when the motor oil is not yet fully circulating.

Benefits

- Reduces harmful friction and excessive heat in both gasoline and diesel-fueled engines
- Formulated with AFMT™ (Anti-Friction Metal Treatment) advanced technology
- Helps protect the engine in the event of oil or coolant loss
- Helps restore engine efficiency to optimize fuel economy
- For both new and older, high-mileage vehicles
- -Free Lifetime Limited Product Engine Warranty
- Will not void manufacturer warranties, compatible in gas or diesel engines



250ml







Automotive Cleaning

Mulit Pupose Cleaner and Stain Remover

Ref:100446

Description

FUKKOL Mulit Pupose Cleaner and Stain Remover It is an emulsion degreasing cleaner, Strong decontamination foam, suitable for cleaning surface stains, foaming fine and rich, and quickly penetrate and decompose stains oil stains, so as toachieve fast and efficient decontamination.

Fragrant smell, containing bactericidal ingredients, inhibiting the growth ofbacteria, convenient and safe to use. It can make the cleaned articles as clean as new, and can remove the dust in every corner and detail, It is widely used for cleaning cars, home furnishings, bathrooms, curtains, carpets, etc.

It can also be used to clean oxide such as yellow robe of machine tool.

Benefits

- -Neutralize the attack of bacterial infection.
- -Strong solubility, eliminate bacterial growth.
- -Mild smell ensures pleasant smell.
- -Effectively remove grease, oil agent, dust, soap scale and dirt.

Cautions

- 1. Suitable for cars, kitchens, glass, toilets, ceramic tiles, floors, carpets, leather, etc.
- It is suitable for degreasing and degreasing cleaning of equipment metal parts of carbon steel, alloy steel, cast steel, stainless steel, aluminum and aluminum alloy.



750ml

Engine Oil

LASER CH-4 ENGINE OIL

Ref:100014-15w/40 100014-30 100014-40

SAE 30.40.15w-40

Laser engine oil is a high-performance, mixed-fleet, shearstable multigrade(SAE 15W-40) automotive diesel engine oil designed for a wide range of diesel and gasoline engines operating under service conditions. It gives superior performance in both diesel and gasoline engines in automotive. transportation, power generation, earth moving and construction services Ref:100016-15w/40

100017-30 100017-40 CHALLENGER CH-4 ENGINE OIL SAE 30,40,15w-40

Challenger engine oil is a high-performance, mixed-fleet, shear-stable multigrade(SAE 15W-40) automotive diesel engine oil designed for a wide range of diesel and gasoline engines operating under service conditions. It gives superior performance in both diesel and gasoline engines in automotive, transportation, power generation, earth moving and construction services.



4L



HYDMASS HEAVY-DUTY TRANSMISSION FLUIDS

ISO 130 6*.10*

Ref:100042-6# 100043-10#

High performance, non friction modified, heavy-duty transmission fluid series designed primarily for powershift transmissions and final drives requiring caterpillar TO-4 fluids.

ANTI-FREEZE ENGINE COOLANT 100%

Ref:100042-6# 100043-10#

A high quality corrosion inhibited ethylene glycol antifreeze liquid for use in internal combustion engine water cooling system.



2L



















Compactors





Articulated Trucks













Road Reclaimers Wheel Tractor-Scrapers





Hydraulic Excavators

Pipelayers

Wheel Loaders

Knuckleboom Loaders





Off-Highway Trucks

Skid Steer Loaders



Track Loaders



















FUKKOL Intercheck crack detection is one kind of RED VISIBLE crack detection method, can detect the cracks of most of metals, ceramic and other materials which are not many

Mould Cleaner I & II

Mould Cleaner I & II, (Fast and Slow dry), this mould cleaner was produced by our special ingredient which is harmless to plastic and rubber materials and actively remove oily surface or impurities. The slow dry formula is special designed for those need to rub the surface and "free time" to adjust individual requirement.

Gas Marks & Gasket Remover

FUKKOL Gasket Remover is a solventbased, high strength cleaner that helps remove baked-on fiber gaskets, gasket adhesives and sealants. It quickly dissolves and aids in the removal of paints, lacquers and varnishes, Gasket Remover contains no methylene chloride

Mould Repair Clay

Soluble Cutting Oil

Mould Repair Clay is a clay act effectively to repair "sand holes", mould crack, leakages in cooling pipes. After 3 hours fully harden, it's equal to hardness as 718 steel materials. Its can be "tapping", grinding and sand blasting. It can replace "traditional welding" Method.

Unpleasant smell, hands irritated, wear and tear to cutting tools, rust on metal is the common problems faced by CNC engineering department. Due to this reason, FUKKOL has created a full system to counter these problems and adjust the formula according to materials, rotation of machine, hardness of metal. Therefore, we can calculate the accurate "cooling effect" for specify

DAC 2 Rust Remover

DAC 2, formulated based on +/- ion chemicals interaction. It will act effectively to remove rust without corrosive to metal surface and harmless to human and environmental friendly.



(Mould Parts Protective Paste) HT paste is a paste formulated by anti-wear and anti-heat additives.

It contains Nano ceramic powder which can stands 1400 ℃. It does prevent "burning" in the mould therefore reduce the workload to exchange and reassemble the mould parts.

HT Paste



FUSI CLEAN

FUKKOL Fusiclean System Cleanser is a nitrite free medium to heavy duty machine. tool cleaner and steriliser, based upon a powerful detergent. It has been specifically formulated to deal with a wide variety of machine tool contaminants and is easy to use with minimum disruption to production. being added direct to the coolant system whilst still in operation. Not applicable to neat oil system.



This mould protector wax based is designed to forms a complete wax-like protective film over the surface of moulds and dies. It's prevents surface contamination on start-up from dissolved deposits between inserts, ejector pins, etc.

Its "self-clean" through plastic injection process therefore save cost and time when reuse the mould.



EDM SUPER

EDM Super is a low viscosity, highly transparent and ROHS qualified product. It is harmless to human and environment friendly. EDM Super could mix with conductive grinding powder or graphite powder to improve the brightness and conductivity.



Hand Torch and MAPP Gas Sets

Stainless Steel and Copper Tapping Oil

This is special formulated by VI additive to easy remove the impurities during "tapping" process, Whereby it is protected the "tapping tool" as well. We have tapping oil which is special for tapping on aluminium & copper materials without corrosive into that materials. This tapping oil is suaitable for "hands-tap" or machine tapping.

Work faster and more efficiently with a higher burn temperature than standard propage. The FUKKOL HT MAPP Gas Hand Torch Cylinder contains premium fuel suited for a variety of job site projects including soldering large copper pipes, brazing and heat treating.Constructed of durable steel, the slim, lightweight cylinder is easy to grip and maneuver. Flame temperature in air is 3,730 degrees Fahrenheit.

www.fukkol-lube.com



"traditional welding" Method

Professional Injection Plastic Chemical Solution MTC Screw Barrel Cleaning Agent is our 15 years of R & D efforts, it's "Reusable" (save cost), fastest time in cleaning process, proven to solve the problems as below black dots Anti Seize Copper changes colours, and Compound difference materials. Anti seize copper compound is a Clean Δ R superior grade assembly compound and high-pressure It is a kind of green acid liquid. lubricant. This high quality copper Mainly used to wipe out scale of based anti-seize formula has silicon and oxide, its metal acid unique particle shapes corrosion inhibitor pretect the suspended in a special carrier. It metal when washing. It can will protect metal parts under used to wipe out the special extreme heat, pressure, and scale in the recycle system contaminating conditions to coolant and thermal switching system and condenser. Mould Release Spray Series We are specializing in Mould Release manufacturing to meet HTM Plastic Elasticizer customer's requirement. It's suitable to use in 80–200°C plastic resin and engineering plastic. This paintable mould release is designed for quick, H.T.M was based on special chemical additives. The medium viscosity is designed oil free, clean releases on with new and recycle plastic material to thermosets and thermoplastics. Will improved. The surface reflet and toughen, and not interfere with post-finishing also provides stability with material. operations; parts can be painted. H.T.M can using with all most plastic that in stenciled, glued, hot stamped, plated compliance with ETV and ASTM norms. or otherwise decorated Absolutely no side effect. Gas Marks & Gasket Remover FUSI CLEAN FUKKOL Gasket Remover is a FUKKOL Fusiclean System Cleanser is a solvent-based, high strength nitrite free medium to heavy duty cleaner that helps remove bakedmachine, tool cleaner and steriliser, based on fiber gaskets, gasket adhesives upon a powerful detergent. It has been and sealants. It quickly dissolves and aids in the removal of paints, specifically formulated to deal with a wide variety of machine tool contaminants and lacquers and varnishes. Gasket is easy to use with minimum disruption to Remover contains no methylene production, being added direct to the chloride. **Mould Protector** coolant system whilst still in operation. Not applicable to neat oil system. (Green) Pigment Disperse Agent This mould protector wax based DAC2 is designed to forms a complete This pigment disperse HT Paste **Rust Remover** wax-like protective film over the (Mould Parts Protective Paste) agent is toxic free and Mould Repair Clay surface of moulds and dies. It's it helps to disperse DAC 2, formulated based on +/prevents surface contamination HT paste is a paste formulated by anti-wear ion chemicals interaction. It will pigment and plastic on start-up from dissolved Mould Repair Clay is a clay act effectively to repair "sand holes", mould crack, leakages in cooling pipes. After 3 hours fully harden, it's equal to hardness as 718 masterbatch. It does and anti-heat additives. It's contains Nano act effectively to remove rust deposits between inserts. without corrosive to metal improve the brightness ceramic powder which can stands 1400°C. ejector pins, etc. Its "self-clean" through plastic injection process and colors uniformity. It does prevent "burning" in the mould therefore reduce the workload to exchange surface and harmless to human and environmental friendly. therefore save cost and time steel materials. Its can be "tapping", and reassemble the mould parts. when reuse the mould. grinding and sand blasting. It can replace



We change Impossible To Possible!



■ HOT LINE

TEL:+86 752 6616270 FAX:+86 752 6616269 OFFICE HOURS:9:00-17:00



■ STOCK CONDITION

TEL:+86 752 6616271 FAX:+86 752 6616269 OFFICE HOURS:9:00-17:00 (MON - FRI)



■ SUGGESTION

clement@fukkol-lube.com



■ TECHNICAL SUPPORT

TEL:+852 24202444 FAX:+852 24851418



■ JOIN US

TEL:+852 24202444 FAX:+852 24851418

www.fukkol-lube.com

Hong Kong Head Office

Kalen International Ltd.

Address: RM 1, 6/F, New Treasure Center, 10 NG Fong Street, San Po Kong Kowloon, Hong Kong

TFI: 0852-24202444 FAX: 0852-24851418

China Factory

Kalen Lubricants Techology (Hui Zhou) Ltd. Tie Chang Precinct Shi Wan Town Bo Luo County Hui Zhou City, Guang Dong, China TEL: 086 752 6616270 FAX: 086 752 6616269

KALEN LUBRICANTS

TECHNOLOGY (THAILAND) LTD.

Address: 72 soi Onnut 25, Onnut, Suan Luang, Bangkok, 10250, Thailand.

TEL: +66 02-1032201

E-mail:sales2@fukkol-lube.com Tax ID:0-1155-60018-74-0



www.fukkol-lube.com