



®

FUKKOL**Nourishment for**
Your Machines

TECHNICAL DATA SHEET

Engine Coolant



200L

18L

4L



Description:

This product is a ethylene glycol based concentrate, which is diluted into a diluent of 50% in volume and can be used for the cooling system of automotive and diesel engines for long service life.

Products Code	Packings	Capacity
LI00021-4L	Can	4L
LI00021-18L	Pail	18L
LI100021-200L	Durm	200L

Purpose :

The cooling system of gasoline, diesel engine.

Performance characteristics:

- Easy to use: it can be used only after diluting the water in a certain proportion.
- The equipment has no fault operation: This product contains effective antirust additives to avoid the rust pollution that seriously affects the performance of the system, and make your equipment run without fault.
- Good temperature performance: the heat dissipation of ethylene glycol / water mixture is strong, and the temperature of the system can be controlled effectively. There will be no hot spot (local overheating) the freezing point of this product is low. So, even under low temperature conditions, there will be no freezing solution.

Typical Physical Properties:

Appearance	PH VALUE	VISCOSITY 40°C mm ² /s	DENSITY 20 °C , g/cm ³	Copper corroded at 100 degrees C, 3h/ grade Not greater than
100% Green transparent liquid	8.5-9.8	10.0-15.0	1.0-1.2	1a