



**FUKKOL**

**Nourishment for**  
**Your Machines**

# TECHNICAL DATA SHEET

## G25-2 SYNTHETIC GRAPHITE PASTE



### Description:

This grease is a plain bearing, roller bearing and ball bearing used to lubricate the workpiece at high temperature. G25-G2 contains fine graphite particles. Carbon free synthetic grease containing non clay, non soap and non abrasive thickening systems. The product has a wide range of use temperature. When the temperature rises (more than 200 degrees), the synthetic base oil can not be evaporated by carbon, leaving only a layer of graphite dry lubricating film. This dry lubricant film naturally adheres to metal components and provides superior lubrication in many harsh conditions.

### Purpose :

Suitable for all kinds of motor, industrial precision instrument, In particular, long term bearing lubrication rolling bearings.

**Applied temperature range :**  
-30°C-600°C

### Performance characteristics :

- multi purpose grease, good lubricity, mechanical stability, chemical stability and water resistance, and also have good high and low temperature performance.

### Typical physical properties:

High speed bearing grease	NLGI	Coning 1/4	Drop point °C	Appearance
Grease 3	3	52~63	≤250	Black ointment

### Matters needing attention 注意事项:

1. Please use it in a suitable temperature range, so as not to cause the grease to freeze or melt.
2. Sealed storage.