



# SDS Safety Data Sheet

## RUSTKING S

### 1. Chemicals and corporate identity

Product identification	FUKKOL RUSTKING S
Product number	12231
Suppliers	KALEN INTERATIONAL LTD Hongkong Kowloon New Po Kong Fong Street No. 10 new treasure Center Building 1 room 6 words
Emergency telephone	+ 852-2420 2444
Fax	+ 852-2485 1418
Manufacturer	KALEN LUBRICANTS TECHNOLOGY (HUI ZHOU) LTD.

### 2. Risk overview

EU standard classification	F; R11   Xn; R65   Xi; R38   R67
GB 13690-92 Classification of common dangerous chemicals	Flammable and explosive hazard: combustible, with a strong reaction can occur.
Physical / chemical hazard	Highly flammable. The material releases steam to form a combustible mixture of gases, which can ignite or explode if ignited. The accumulation of static electricity in the substance may cause a fire to discharge.
Health hazard	Harmful: If endocytosis can cause damage to the lungs. Steam can cause drowsiness and dizziness. It may stimulate the eyes, nose, larynx, and lungs. May cause depression in the central nervous system.
Environmental hazard	It is harmful to aquatic organisms and may cause long-term adverse effects on aquatic environment.

Flame burst hazard

Combustible goods.

Danger sign



### 3. Composition

Ingredients	CAS #	Proportion
Hydrocarbons and their derivatives	64771-72-8	15.0 - 35.0%
Alkanes and isomers	64742-48-9	15.0 - 25.0%
Propane and its mixture	68476-85-7	40.0 - 50.0%
Antirust additive	-----	18.0 - 30.0%

### 4. First aid measures

<b>Inhalation</b>	Using appropriate respiratory protective device, the patient will be transferred immediately, if the patient stops breathing, artificial respiration should be carried out, and the rest is maintained and the medical care is carried out in time.
<b>Skin contact</b>	Wash the place with soap and water. Take off contaminated clothes. Contaminated clothes should be washed with soap and water and then wear.
<b>Eye contact</b>	To wash the eyelids, with the flow of water or saline. Seek medical assistance
<b>Eating</b>	If the victim is lighter, drink 2-4 cup of milk or water. If the victim has lost consciousness, seek medical attention immediately.

### 5. Fire control measures

<b>Fire Extinguisher</b>	Use foam, dry chemical reagent (dry powder), or carbon dioxide (CO <sub>2</sub> ) fire.
--------------------------	---



# SDS Safety Data Sheet

Hazardous combustion  
products

Carbide, hydride, water

Not listed

Flash point (degrees C)  
Fire extinguishing  
procedure

Firefighters to wear a gas mask, wearing a full body fire service, in the upper hand to fire. As far as possible the containers from fire to open. Water spray to keep fire cooling container, until the end of the fire. If the containers in the fireground have discoloration or generate sound from the safety relief devices, must be immediately evacuated.

Fire extinguishing agent: foam, dry powder, carbon dioxide, sand.

## 6. Accidental overflow handling measures

High temperature of the material, to avoid fire, Mars, or natural fire, if there is no danger, it is possible to stop and then overflow. With a mop or absorbent material will overflow into the proper container for further processing. Quickly evacuate the contaminated area personnel to the safe area, and to isolate, strictly limit access. Cut off the fire source. Recommended emergency personnel wear self positive pressure respirator, wear protective clothing for firefighters. As far as possible to cut off the source of leakage, prevent access to sewers, flood channel limited space.

Small leakage

Small leakage: adsorption or absorption of sand or other non combustible materials. Can also be used a lot of water washing, washing water and diluted into the wastewater system.

Large leakage

Large leakage: construct a barrierpit to contain; covered with foam, reduce the Vapor Hazard. Explosion proof pump transferred to tankexclusive collector, place the disposal of recycling or shipped to the waste disposal.

## 7. Operation disposal and storage

Operating notes

Closed operation, pay attention to ventilation. Operators must be trained in strict compliance with the operating rules. Stay away from fire, heat, smoking is prohibited in the workplace. Use explosion-proof ventilation system and equipment. To prevent vapor from leaking into the air in the workplace. Avoid contact with oxidizing agent. When transporting light light, to prevent damage to

packaging and containers.

Mechanical equipment and tools that are prohibited from using the easy to produce sparks.

At the time of filling, we should pay attention to the velocity of flow (not more than 3m/s), and there is a grounding device to prevent the accumulation of static electricity.

Stored in a cool, ventilated warehouse. Away from fire and heat. The temperature in the warehouse is not more than 45. To prevent direct sunlight. Keep container seal. Should be separate from the oxidant. Storage room lighting, ventilation and other facilities should be used in explosion-proof type, switch located in the warehouse. Equipped with corresponding varieties and quantities of fire equipment. Bottled stacking is not too large, should stay away from the wall, from the top of column, and the necessary fire inspection walkway. Technical measures for fire and explosion prevention in the storage tank. Open tank to summer cooling measures.

### Storage precautions

## 8. Exposure control and personal protection

### Occupational exposure limit

material	CAS NO	category	numerical value	form
Hydrocarbons and their derivatives	64771-72-8	Short-term emissions	1600mg/m3	Fog
Propane and its mixture	68476-85-7	Short-term emissions	1800mg/m3	Fog

### Chemical marking symbol



### Process control

Production process closed, full ventilation. Provide safe shower and eye washing equipment.

### Inhalation

Respiratory system protection  
Generally do not need special protection, but the working environment of the air concentration than the general situation, can be worn with a filter type gas mask (half mask).



# SDS Safety Data Sheet

Personal protection The body is protected against static electricity. Hand  
protective wear gloves.

Its Smoking is prohibited in the workplace.

## 9. Physical and chemical properties

Product status	Liquid state
Appearance and smell	Clear yellow liquid with slight solvent odor
Specific gravity 25, g/cm <sup>3</sup>	0.750-0.850
Antirust period	Room temperature 1-2 years
Solubility Volatile organic compounds (%) g/l: 0	Insoluble in water, Miscible with organic solvents lbs./gal:0
Copper chip corrosion is not greater than	1a

## 10. Stability and chemical reaction data

Stability	Stable
Risk aggregation	Will not produce
Avoid measures	Strong oxidant, acid, amine, anhydride
Material attention	No
The risk of material after decomposition	No

## 11. Toxicity data

Acute toxicity: Genuine leather LD50 Murine vein Township 40mg/kg



# SDS

## Safety Data Sheet

Inhalation LC50

4 hours (rats inhaled)

3400ppm

When skin tests are performed on animals, it is found that long-term exposure can cause skin sensitivity, but they are mild or moderate.  
In contact with the product, such as the use of water wash should be no big deal, but also to try to avoid prolonged contact or inhalation of this product.

### 12. Ecological data

Ecological toxicity No data display

Environmental degradation No data display

### 13. Waste information

Waste method

The empty drum shall be recovered, regenerated or abandoned by the institution of a qualified or executing license, and be careful in any case to make sure that it is in conformity with the national laws and local regulations.

### 14. Transport information

Maritime name Aerosol

Dangerous goods category Class 2.1 flammable and explosive gases

United Nations Code UN1950

Package type II

Label 2

Hazardous substances needed to be reported Unwanted

Special preparation for transportation Unwanted

### 15. Regulation information



# SDS

## Safety Data Sheet

EU standard  
classification

Combustible  
The classification of the product is carried out according to  
the test data of the whole or part of the product.

EU label

Symbol: F, Xn

Risk characteristics

R11; Flammable.  
R67; Steam can cause drowsiness and dizziness.  
S43; In case of fire, use foam, dry chemical preparation (dry  
powder) or carbon dioxide

Safety recommendations

S9; Place the container in a well ventilated place.  
S16; Stay away from fire, please do not smoke.  
S33; Take ESD preventive measures.  
S36/37; Wear suitable protective clothing and gloves.  
S57; Use appropriate containers to avoid environmental  
pollution  
S60; This material and its container must be treated with  
hazardous waste.

## 16. Other information

Reference:

Change description: No

Other information: The following laws and regulations and standards have made  
corresponding regulations on the safe use, storage, transportation, loading and  
unloading, classification and marking of chemicals.:

Law Of The People's Republic Of China On Safe Production. (The tenth meeting of the  
standing committee of the 12th National People's Congress was adopted in  
Aug., 31th, 2014)

The Occupational-Disease-Prevention Law Of The People's Republic Of China. (The 24th  
meeting of the standing committee of the ninth National People's Congress was adopted  
in Oct., 27th, 2001)

Environmental Protection Law Of The People's Republic Of China. (The 11th meeting of  
the standing committee of the seventh National People's Congress was adopted in  
Dec., 26th, 1989.)

Regulations On The Safety Management Of Hazardous Chemicals. (The 44th executive  
meeting of the state council adopted the amendment in Feb., 16th, 2011.)

《The safety production license ordinance.》 (The 34th executive meeting of the state  
council adopted in Jan., 7th, 2004.)

Disclaimer.:



## SDS Safety Data Sheet

The content of this material safety data is taken from the source of the company's reliable sources. However, the information provided by the content of these information, the company has not included any guarantee, presentation and implied. For the operation, storage, use and disposal of this product, the environment has exceeded the scope of the company's cognition, and the company does not assume responsibility for any operation, storage, use and disposal of any operation, storage, use and disposal of the products related to this product. This material safety data is prepared for this purpose and can only be used for this product, when the product is used as a component of the other products, and can not be applied to the material safety data.

Release date: May, 1st, 2020