



富高

FUKKOL

一切決擇於潤滑

产品描述及数据参数

MOULD RELEASE SERIES FUKKOL MOULD RELEASE AGENT NON-PAINTABLE



Description:

High oil demoulding agent is a highly efficient spray demoulding agent, which provides fast, effective and non polluting molding for plastic and rubber products formed by most injection moulds. The specially designed nozzle can produce very fine spray effect, and the spraying quantity can be completely controlled, even the most complicated mold cavity can be completely covered.

Precautions:

Pressure vessels to avoid direct sunlight exposure, stored at temperatures below 50 degrees.
Do not stamp or burn the container
It should not be sprayed to the surface of a flame or incandescent metal
Inflammable Materials.

Products Code	Packings	Capacity
I17791-500ML	Can.	500ML
I17791-18L	Pail	18L
I17791-200L	Dum.	200L

Performance Characteristics:

- Hyperfine injection makes the whole die fully covered
- Increase the degree of smoothness and reduce the risk of overspraying
- Reduce the problems caused by marking and transportation, quick and effective demoulding and economic benefits. It can be demolde many times with only one spray.
- The highly effective and durable lubricating film can provide multiple demoulding, better than other silicone formulations.
- Little environmental impact, no chlorinated fluorocarbon (CFC) propellant.
- Non polluting characteristics are excellent lubricants commonly used in textile and paper industry.

Typical Physical Properties:

APPEARANCE	ODOR	COPPER CORROSION 100 °C, 3 hrs	DENSITY 25 °C , g/cm ³
Water clear	Solvent taste	1a	0.7~0.75