



®


Nourishment for
Your Machines

FUKKOL

TECHNICAL DATA SHEET



Power lub



Description:

The thimble oil, refined from crude oil, contains a lot of extreme pressure additives. It can be used for high load sliding part and plastic top pin.

Purpose :

- Suitable for rail lubrication of machined machinery under various speeds and loads.
- Especially suitable for the central lubrication system
- It is a widely used lubricating product which is suitable for machining machine parts (hydraulic, guideway, gear device).
- Designed for use with steel / copper and steel / pig iron tool guides.
- It also applies to hydraulic systems with the same hydraulic and guide lubrication systems.
- It can be used for plastic top needle.

Performance characteristics:

- High quality lubricants with good oxidation stability. Oil-bearing agent, anti wear and adhesion additives, it can prevent the mechanical rail and slide surface of the tool from slipping during operation.
- Protect the cutting tool to expose the parts from the corrosion
- Completely lossless on the oil seal
- Excellent performance of anti emulsification
- Excellent antioxidant properties
- Excellent rust protection and protection performance

Products Code	Packings	Capacity
I11448-500ML	Can.	500ML
I11448-18L	Pail	18L
I11448-200L	Dum.	200L

Typical physical properties

Product	11448 Power Lub
Appearance	Brown yellow transparent liquid
Density 25°C, g/cm ³	0.73
Copper corrosion 100°C 3h	1a
Water solubility	Insoluble in water
Propellant	LPG

Matters needing attention :

1. pressure vessels, avoid direct sunlight, stored at below 50 degrees Celsius.
2. should not be sprayed to the flame. Do not stamp or burn the container.
3. this product is flammable.