



SDS Safety Data Sheet

RUST REMOVER

1. Chemicals and corporate identity

Product identification	FUKKOL DAC 2 RUST REMOVER
Product number	100078
Suppliers	KALEN INTERATIONAL LTD Hongkong Kowloon New Po Kong Fong Street No. 10 new treasure Center Building 1 room 6 words
Emergency telephone	+ 852-2420 2444
Fax	+ 852-2485 1418
Manufacturer	KALEN LUBRICANTS TECHNOLOGY (HUI ZHOU) LTD.

2. Risk overview

EU standard classification	-----
GB 13690-92 Classification of common dangerous chemicals	Not belong
Physical / chemical hazard	SEM Risco de USO normal.
Environmental hazard	The environment is harmful, may cause long-term adverse effects on aquatic environment.
Health hazard	The invasive route is inhalation, ingestion and transdermal absorption. Steam can cause drowsiness and dizziness. The accumulation of steam will flicker or explode if it is ignited.
Flame burst hazard	This product is not flammable.

Danger sign



3. Composition

Ingredients	CAS #	Proportion
Deionized water	7732-18-5	60.0 – 75.0%
Alcohol based C12-15 vinyl ether and its derivatives	68131-19-5	20.0 – 35.0%
Metal corrosion inhibitor	----	2.5 – 6.0%
Cleaning anti oxygen additive	----	8.5 – 10.0%

4. First aid measures

Inhalation	Using appropriate respiratory protective device, the patient will be transferred immediately, if the patient stops breathing, artificial respiration should be carried out, and the rest is maintained and the medical care is carried out in time. .
Skin contact	Wash the place with soap and water. Take off contaminated clothes. Contaminated clothes should be washed with soap and water and then wear.
Eye contact	To wash the eyelids, with the flow of water or saline. Seek medical assistance
Eating	If the victim is lighter, drink 2-4 cup of milk or water. If the victim has lost consciousness, seek medical attention immediately.

5. Fire control measures

Fire Extinguisher	not applicable
Hazardous combustion products	NO



SDS Safety Data Sheet

Flash point (degrees C)
Fire extinguishing
procedure

Not listed
not applicable

6. Accidental overflow handling measures

High temperature of the material, to Avoid human contact, if there is no danger, it is possible to stop and then overflow. With a mop or absorbent material will overflow into the proper container for further processing.

Quickly evacuate the contaminated area personnel to the safe area, and to isolate, strictly limit access. Cut off the fire source. Recommended emergency personnel wear self positive pressure respirator, wear protective clothing for firefighters. As far as possible to cut off the source of leakage, prevent access to sewers, flood channel limited space.

Small leakage

Adsorption or absorption of sand or other non combustible materials. can also be washed with plenty of water and diluted with water after washing into the waste water system.

Large leakage

Construct a barrierpit to contain; covered with foam, reduce the Vapor Hazard. Explosion proof pump transferred to tankexclusive collector, place the disposal of recycling or shipped to the waste disposal.

7. Operation disposal and storage

Operating notes

Closed operation, pay attention to ventilation. Operators must be trained in strict compliance with the operating rules. Stay away from fire, heat, smoking is prohibited in the workplace. Use explosion-proof ventilation system and equipment. To prevent vapor from leaking into the air in the workplace. Avoid contact with oxidizing agent. When transporting light light, to prevent damage to packaging and containers.

Mechanical equipment and tools that are prohibited from using the easy to produce sparks.

At the time of filling, we should pay attention to the velocity of flow (not more than 3m/s), and there is a grounding device to prevent the accumulation of static electricity.

Storage precautions

Stored in a cool, ventilated warehouse. Away from fire and heat. The temperature in the warehouse is not more than 45. To prevent direct sunlight. Keep container seal. Should be separate from the oxidant. Storage room lighting, ventilation and other facilities

should be used in explosion-proof type, switch located in the warehouse. Equipped with corresponding varieties and quantities of fire equipment. Bottled stacking is not too large, should stay away from the wall, from the top of column, and the necessary fire inspection walkway. Technical measures for fire and explosion prevention in the storage tank. Open tank to summer cooling measures.

8. Exposure control and personal protection

Occupational exposure limit

Temporary database display

Chemical marking symbol



process control

Production process closed, full ventilation. Provide safe shower and eye washing equipment.

Inhalation

Respiratory system protection
Generally do not need special protection, but the working environment of the air concentration than the general situation, can be worn with a filter type gas mask (half mask).

Personal protection

Body protection Wear anti-static work clothes.
Hand protection Wear general protective gloves.

Its

Smoking is prohibited in the workplace.

9. Physical and chemical properties

Product status

liquid

Appearance and smell

Light red and special smell

Specific gravity 25°C,
g/cm³

0.95-1.05



SDS Safety Data Sheet

PH

<2

Solubility
Volatile organic
compounds (%)
g/l: 0

Dissolve in water and do not dissolve with organic solvents
0
lbs./gal:0

10. Stability and chemical reaction

Stability

Stable

Risk aggregation

Will not produce

Avoid measures

Strong oxidizing agent, alkali, alkali anhydride

Material attention

No

The risk of material
after decomposition

No

11. Toxicity data

1. When skin tests are performed on animals, it is found that long-term exposure can cause skin sensitivity, but they are mild or moderate. When drinking, it may lead to diarrhea and vomiting. When you enter the eye, it may cause inflammation.
2. In contact with the product, such as the use of water wash should be no big deal, but also to try to avoid prolonged contact or inhalation of this product.

12. Ecological data

Ecological toxicity

No data display

Environmental degradation

No data display

13. Waste information

Waste method

The empty drum shall be recovered, regenerated or abandoned by the institution of a qualified or executing license, and be careful in any case to make sure that it is in conformity with the national laws and local regulations.

14. Transport information

Transport mode	Transport by ordinary product.
Packing method	Plastic barrels; plastic bottles; iron.
Transportation matters needing attention	The corresponding variety and quantity of fire fighting equipment and leakage emergency treatment equipment should be equipped with the corresponding variety and quantity of the transport vehicle. It's better to transport early and late in summer. The tank (tank) used in transportation should be connected with the chain, and the holes can be arranged in the groove to reduce the vibration and generate static electricity. With no oxidant edible chemical conventional mixing luck. Transit should prevent accumulation of insolation, rain, high temperature resistant. Should stay away from the fire, heat, high temperature zone. The vehicle exhaust pipe of the vehicle must be equipped with a fire resistance device, which prohibits the use of easy to produce sparks of machinery and equipment and tools for loading and unloading.

15. Regulation information

EU standard classification	Non combustible. The classification of the product is carried out according to the test data of the whole or part of the product.
EU label	-----
Risk characteristics	R65; harmful: If swallowing can cause lung injury. S9; Place the container in a well ventilated place. S16; Stay away from fire, please do not smoke. S33; Take ESD preventive measures.
Safety recommendations	S36/37; Wear suitable protective clothing and gloves. S57; Use appropriate containers to avoid environmental pollution S60; This material and its container must be treated with hazardous waste.



SDS Safety Data Sheet

S62; after eating do not induce vomiting: seek medical advice immediately and show this container or its logo.

16. Other information

Reference:

Change description: No

Other information: The following laws and regulations and standards have made corresponding regulations on the safe use, storage, transportation, loading and unloading, classification and marking of chemicals.:

Law Of The People's Republic Of China On Safe Production. (The tenth meeting of the standing committee of the 12th National People's Congress was adopted in Aug., 31th, 2014)

The Occupational-Disease-Prevention Law Of The People's Republic Of China. (The 24th meeting of the standing committee of the ninth National People's Congress was adopted in Oct., 27th, 2001)

Environmental Protection Law Of The People's Republic Of China. (The 11th meeting of the standing committee of the seventh National People's Congress was adopted in Dec., 26th, 1989.)

Regulations On The Safety Management Of Hazardous Chemicals. (The 44th executive meeting of the state council adopted the amendment in Feb., 16th, 2011.)

《The safety production license ordinance.》 (The 34th executive meeting of the state council adopted in Jan., 7th, 2004.)

Disclaimer.:

The content of this material safety data is taken from the source of the company's reliable sources. However, the information provided by the content of these information, the company has not included any guarantee, presentation and implied. For the operation, storage, use and disposal of this product, the environment has exceeded the scope of the company's cognition, and the company does not assume responsibility for any operation, storage, use and disposal of any operation, storage, use and disposal of the products related to this product. This material safety data is prepared for this purpose and can only be used for this product, when the product is used as a component of the other products, and can not be applied to the material safety data.

Release date: May, 1st, 2020