



FUKKOL

Nourishment for
Your Machines

TECHNICAL DATA SHEET

Gas marks & gasket remover



Description:

The rich and high mold, gill stain cleaning agent is solvent type, high strength degreasing agent, effectively removes gasket rubber and gasket sealant. It can dissolve or remove paint, varnish, adhesive and metal paint.

Purpose:

Effective removal of motor, pump, flange basin and other gaskets, and can also remove paint. Adhesive, painting, removal of metal surface and stone surface.

Advantage:

- It can quickly remove gaskets, plastic rings, locking glue and sealing rings.
- Loose carbon residue can be loosened.
- To protect the surface of the equipment by reducing excessive scraping.
- Excellent paint scavenger
- No dichloromethane

Products Code	Packings	Capacity
I66866-500ML	Can.	500ML
I66866-18L	Pail	18L
I66866-200L	Dum.	200L

Typical physical properties

Product	66866 Gas marks & gasket remover
Appearance	Colorless Transparent Liquid
Density 25°C, g/cm ³	0.72-0.76
Copper corrosion 100°C 3h	1a
Product	Insoluble in water
Appearance	LPG

Matters needing attention

1. pressure vessels, avoid direct sunlight, stored at below 50 degrees Celsius.
2. should not be sprayed to the flame. Do not stamp or burn the container.
3. this product is flammable.